

# RS 4-14

CONSTRUCTION TELEHANDLERS



## Key Features

- ✓ Four-wheel Drive/Four-Wheel Steer
- ✓ Universal Skid Steer Attach System Standard
- ✓ Manitou Quick Attach Optional

## Key Specifications

- ✓ 4,400 lbs. (1996 kg) maximum lift capacity
- ✓ 14' 3" (4.35 m) maximum lift height
- ✓ 4,400 lbs. (1996 kg) lift capacity to 14' 3" (4.35 m)
- ✓ 56.3 hp (42 kW) Kubota diesel engine

## SPECIFICATIONS

		IMPERIAL	METRIC
Capacities	Max. capacity	4400 lb	1995.81 kg
	Max. lifting height	14 ft 3 in	4.34 m
	Maximum outreach	9 ft	2.74 m
	Breakout force with bucket	1886 daN	1886 daN
Weight and dimensions	Overall length to carriage	11 ft 11 in	3.64 m
	Length to face of forks	11 ft 9 in	3.58 m
	Overall width	4 ft 11 in	1.49 m
	Overall height	6 ft 3 in	1.91 m
	Wheelbase	7 ft	2.13 m
	Ground clearance	9 in	0.24 m
	Overall cab width	2 ft 7 in	0.80 m
	Tilt-up angle	12 °	12 °
	Tilt-down angle	116 °	116 °
	External turning radius (over tyres)	10 ft 1 in	3.07 m
	Unladen weight (with forks)	9237 lb	4190 kg
	Overall weight	9237 lb	4189.83 kg
	Tires type	Pneumatic	Pneumatic
	Tires brand	Kubota	Kubota
Engine	Engine norm	Stage V	Stage V
	Engine model	2607-CR-E5	2607-CR-E5
	Number of cylinders / Capacity of cylinders	4 - 160 in³	4 - 2615 cm³
	I.C. Engine power rating - Power	56.30 Hp / 42 kW	56.30 Hp / 42 kW
	Max. torque / Engine rotation	128 ft/lbs @ 2700 rpm	174 Nm @ 2700 rpm
	Drawbar pull	2850 daN	2850 daN
	Drawbar pull (Laden)	2850 daN	2850 daN
Transmission	Transmission type	Hydrostatic	Hydrostatic
	Number of gears (forward / reverse)	2 / 2	2 / 2
	Max. travel speed	16 mph	25 km/h
	Max. travel speed (may vary according to applicable regulations)	15 mph	24.90 km/h
	Parking brake	Automatic Negative Hand-brake	Automatic Negative Hand-brake
	Service brake	Disk brake on the cadran shaft	Disk brake on the cadran shaft
	Axle Manufacturer	Dana	Dana
Hydraulics	Hydraulic pump type	Gear pump	Gear pump
	Hydraulic flow / Pressure	20 US gpm-3408 PSI	77.41 l/min-235 bar
Tank capacities	Engine oil	3 US gal	10.20 l
	Hydraulic oil	18 US gal	68.14 l
	Fuel tank	16 US gal	60 l
Miscellaneous	Steering wheels (front / rear)	2 / 2	2 / 2
	Drive wheels (front / rear)	2 / 2	2 / 2
	Safety / Cab certification	Standard EN 15000 / ROPS/FOPS	Standard EN 15000 / ROPS/FOPS
	Controls	Single Joystick FNR	Single Joystick FNR



Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



One Gehl Way, West Bend, WI 53095  
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT