

RS 4-14

CONSTRUCTION TELEHANDLERS



Key Features

- ✓ Four-wheel Drive/Four-Wheel Steer
- ✓ Universal Skid Steer Attach System Standard
- ✓ Manitou Quick Attach Optional

Key Specifications

- ✓ 4,400 lbs. (1996 kg) maximum lift capacity
- ✓ 14' 3" (4.35 m) maximum lift height
- ✓ 4,400 lbs. (1996 kg) lift capacity to 14' 3" (4.35 m)
- ✓ 56.3 hp (42 kW) Kubota diesel engine

SPECIFICATIONS

		IMPERIAL
Capacities	Max. capacity	4400 lb
	Max. lifting height	14 ft 3 in
	Max. outreach	9 ft
	Breakout force with bucket	1886 daN
Weight and dimensions	Overall length to carriage	11 ft 11 in
	Length to face of forks	11 ft 9 in
	Overall width	4 ft 11 in
	Overall height	6 ft 3 in
	Wheelbase	7 ft
	Ground clearance	9 in
	Overall cab width	2 ft 7 in
	Tilt-up angle	12 °
	Tilt-down angle	116 °
	External turning radius (over tyres)	10 ft 1 in
	Unladen weight (with forks)	9237 lb
	Overall weight	9237 lb
	Tires type	Pneumatic
	Engine	Engine brand
Engine norm		Stage V
Engine model		2607-CR-E5
Number of cylinders / Capacity of cylinders		4 - 160 in ³
I.C. Engine power rating - Power		56.30 Hp / 42 kW
Max. torque / Engine rotation		128 ft/lbs @ 2700 rpm
Drawbar pull		2850 daN
Drawbar pull (Laden)		2850 daN
Transmission	Transmission type	Hydrostatic
	Number of gears (forward / reverse)	2 / 2
	Max. travel speed	16 mph
	Max. travel speed (may vary according to applicable regulations)	15 mph
	Parking brake	Automatic Negative Hand-brake
	Service brake	Disk brake on the cadran shaft
Hydraulics	Axle Manufacturer	Dana
	Hydraulic pump type	Gear pump
Tank capacities	Hydraulic flow / Pressure	20 US gpm-3408 PSI
	Engine oil	3 US gal
	Hydraulic oil	18 US gal
Miscellaneous	Fuel tank	16 US gal
	Steering wheels (front / rear)	2 / 2
	Drive wheels (front / rear)	2 / 2
	Safety / Safety cab homologation	Standard EN 15000 / ROPS/FOPS
Controls	Single Joystick FNR	



Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



One Gehl Way, West Bend, WI 53095
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT