

# RS 5-19 GEN:3

CONSTRUCTION TELEHANDLERS



## Key Features

- ✓ Four-wheel Drive/Four-wheel Steer
- ✓ Compact size - Less than 6' wide and under 6' 5" tall
- ✓ Able to lift and place most palletized loads
- ✓ 10,000 lb. empty vehicle weight

## Key Specifications

- ✓ 5,500 lbs. (2495 kg) maximum lift capacity
- ✓ 19' 1" (5.8 m) maximum lift height
- ✓ 3,000 lbs. (1361 kg) lift capacity to 19' 1" (5.8 m)
- ✓ 69 hp (50.1 kW) Yanmar diesel engine

## SPECIFICATIONS

		IMPERIAL	METRIC
Capacities	Max. capacity	5500 lb	2494.76 kg
	Max. lifting height	19 ft 1 in	5.82 m
	Maximum outreach	11 ft	3.35 m
Weight and dimensions	Length to face of forks	12 ft 4 in	3.76 m
	Overall width	5 ft 11 in	1.80 m
	Overall height	6 ft 4 in	1.93 m
	Wheelbase	7 ft 6 in	2.29 m
	Ground clearance	10 in	266 mm
	Overall cab width	28 in	711 mm
	Tilt-up angle	12 °	12 °
	Tilt-down angle	100 °	100 °
	External turning radius	11 ft	3.35 m
	Unladen weight (with forks)	9760 lb	4427 kg
	Overall weight	10000 lb	4535.92 kg
	Standard tires	12 x 16.5	12 x 16.5
Performances	Lifting	8 s	8 s
	Lowering	5 s	5 s
	Extension	7 s	7 s
	Retraction	6 s	6 s
Engine	Engine brand	Yanmar	Yanmar
	Engine norm	Tier 4 final	Tier 4 final
	Engine model	4TNV98C	4TNV98C
	I.C. Engine power rating - Power	69 Hp / 50.10 kW	69 Hp / 50.10 kW
Transmission	Max. torque / Engine rotation	173 ft/lbs @ 1625 rpm	235 Nm @ 1625 rpm
	Transmission type	Hydrostatic	Hydrostatic
	Number of gears (forward / reverse)	2 / 2	2 / 2
	Max. travel speed	15 mph	24 km/h
	Parking brake	Hydraulic spring release SAHR	Hydraulic spring release SAHR
	Service brake	Wet disc brakes	Wet disc brakes
	Axle Manufacturer	Dana	Dana
Hydraulics	Hydraulic pump type	Gear pump	Gear pump
	Hydraulic flow / Pressure	22 US gpm-3350 PSI	83.28 l/min-231 bar
Tank capacities	Engine oil	2 US gal	9 l
	Hydraulic oil	18 US gal	68.14 l
	Fuel tank	17 US gal	64.35 l
Miscellaneous	Steering wheels (front / rear)	2 / 2	2 / 2
	Drive wheels (front / rear)	2 / 2	2 / 2
	Cab certification	ROPS/FOPS	ROPS/FOPS
	Controls	Single Joystick FNR	Single Joystick FNR



## STANDARD FEATURES

- Four Wheel Drive
- Boom Tip Lift Hook
- Two-Speed Hydrostatic Drive System
- Back-Up Alarm
- Engine Block Heater
- 12Volt Power Port
- 12 Volt Battery
- Self-Leveling Forks
- Multi-Function Display Screen

## OPTIONAL FEATURES

- Suspension Seat
- Light Package - LED
- Turf Tires
- Solid Rubber Tires
- Foam Filled Tires
- Enclosed Cab with Heat and A/C
- Easy Manager

Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



One Gehl Way, West Bend, WI 53095  
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT