

# RT105

# TRACK LOADERS



# GEHL®

| Capacities                               |     | Imperial            |
|--|-----|---------------------|
| Operating Weight                         |     | 4720 lb             |
| Operating Capacity at 35% Tipping Load   |     | 1049 lb             |
| Operating Capacity At 50% Tipping Load   |     | 1499 lb             |
| Weight and dimensions                    |     |                     |
| Overall Operating Height - Fully Raised  | h27 | 144 in              |
| Height to Hinge Pin – Fully Raised       | h28 | 109 in              |
| Reach - Fully Raised                     | dp1 | 26 in               |
| Dump angle at full height                | a5  | 38 °                |
| Dump Height - Fully Raised               | h29 | 84 in               |
| Maximum Rollback Angle - Fully Raised    | a4  | 102 °               |
| Overall Height to top of ROPS            | h17 | 71 in               |
| Overall length with bucket               | l16 | 118 in              |
| Overall Length without Bucket            | l1  | 89 in               |
| Specified Height                         | h31 | 58 in               |
| Reach at Specified Height                | r4  | 39 in               |
| Dump angle at specified height           | a17 | 72 °                |
| Maximum Rollback Angle at Ground         | a13 | 32 °                |
| Carry Position                           | d5  | 5 in                |
| Maximum Rollback Angle at Carry Position | a14 | 32 °                |
| Digging Position                         | h32 | 0 in                |
| Ground clearance                         | m4  | 8 in                |
| Track gauge                              | b10 | 41 in               |
| Track Shoe Width                         | b20 | 10 in               |
| Crawler base                             | y2  | 51 in               |
| Overall width less bucket                | b1  | 51 in               |
| Bucket Width                             | e1  | 54 in               |
| Clearance Radius - Front with Bucket     | b18 | 73 in               |
| Clearance Circle - Rear                  | wa1 | 51 in               |
| Track Type / Track Rollers / Roller Type |     | Rubber / 3 / Steel  |
| Performances                             |     |                     |
| Ground Speed - Single Speed              |     | 6 mph               |
| Engine                                   |     |                     |
| Engine brand                             |     | Yanmar              |
| Engine model                             |     | 3TNV88C             |
| Gross Power / Power                      |     | 25.50 kW @ 2800 rpm |
| Battery voltage                          |     | 12 V                |
| Cold Cranking Amps at Temperature (CCA)  |     | 800 A               |
| Alternator - Voltage / Ampere            |     | 12 V / 55 A         |
| Hydraulics                               |     |                     |
| Standard flow - Auxiliary hydraulics     |     | 15 US gpm           |
| Tank capacities                          |     |                     |
| Hydraulic tank capacity                  |     | 8 US gal            |
| Fuel tank                                |     | 10 US gal           |
| Displacement                             |     | 0.43 US gal         |

## Equipment

| Lifting function                                  |          |
|---|----------|
| All-Tach® Attachment Mounting System              | Standard |
| Operator station                                  |          |
| Foot and Hand Throttles (Dual Joystick and T-bar) | Standard |
| Security  |          |
| Hour meter  | Standard |



# GEHL®

Siège Social  
P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095  
Tel: (262) 334-9461 - Fax: (262) 338-7517  
[www.gehl.com](http://www.gehl.com)



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend