TRACK LOADERS



GEHL®

	kilos cieduo et	27 de julio de 2024, 05:31:00
Capacities		Métrico
Operating Weight		2141 kg
Operating Capacity at 35% Tipping Load		476.27 kg
Operating Capacity At 50% Tipping Load		680 kg
Tipping capacity		1361 kg
Weight and dimensions		
Overall Operating Height - Fully Raised	h27	3650 mm
Height to Hinge Pin – Fully Raised	h28	2769 mm
Reach - Fully Raised	dp1	673.10 mm
Dump angle at full height	a5	38°
Dump Height - Fully Raised	h29	2134 mm
Maximum Rollback Angle - Fully Raised	a4	102 °
Overall Height to top of ROPS	h17	1816 mm
Overall length with bucket	l16	2985 mm
Overall Length without Bucket	l1	2258 mm
Specified Height	h31	1466 mm
Reach at Specified Height	r4	991 mm
Dump angle at specified height	a17	72 °
Maximum Rollback Angle at Ground	a13	32 °
Carry Position	d5	127 mm
Maximum Rollback Angle at Carry Position	a14	32 °
Digging Position	h32	0 mm
Ground clearance	m4	191 mm
Track gauge	b10	1039 mm
Track Shoe Width	b20	250 mm
Crawler base		1283 mm
	y2 b1	1283 IIIII 1290 mm
Overall width less bucket Bucket Width		
	e1	1372 mm
Clearance Radius - Front with Bucket	b18	1854 mm
Clearance Circle - Rear	wa1	1290 mm
Track Type / Track Rollers / Roller Type		Rubber / 3 / Steel
Performances		
Ground Speed - Single Speed		10.10 km/h
Engine		
Engine brand		Yanmar
Engine model		3TNV88C
Gross Power / Power		25.50 kW @ 2800 rpm
Battery voltage		12 V
Cold Cranking Amps at Temperature (CCA)		800 A
Alternator - Voltage / Ampere		12 V / 55 A
Hydraulics		
Standard flow - Auxiliary hydraulics		55 l/min
Tank capacities		
Hydraulic tank capacity		30 l
Fueltank		36 l
Displacement		1.64 l

Equipamiento

Lifting function	
All-Tach® Attachment Mounting System	Estándar
Operator station	
Foot and Hand Throttles (Dual Joystick and T-bar)	Estándar
Security	
Hour meter	Estándar





Siège Social P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095 Tel: (262) 334-9461 - Fax: (262) 338-7517 www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend