

# RT135

## COMPACT LOADERS



### Key Features

- ✓ Compact Dimensions
- ✓ Pilot Joystick Controls
- ✓ IdealTrax™ Automatic Track Tensioning
- ✓ All-Tach™ Attachment System (Universal Type)
- ✓ ROPS/FOPS Level II

### Key Specifications

- ✓ 1,350 lbs. (612 kg) Rated Operating Capacity (35%)
- ✓ 46.4 hp (35 kW) Yanmar Engine Stage 3A
- ✓ 110" (2794 mm) Height to Hinge Pin
- ✓ 57" (1448 mm) Overall Machine Width
- ✓ 76" (1930 mm) Overall Height

SPECIFICATIONS

		IMPERIAL	METRIC
Capacities	Operating Weight	6510 lb	2953 kg
	Operating Capacity at 35% Tipping Load	1350 lb	612.35 kg
	Operating Capacity At 50% Tipping Load	1929 lb	875 kg
	Tipping capacity	3858 lb	1750 kg
Weight and dimensions	Overall Operating Height - Fully Raised	144 in	3670 mm
	Height to Hinge Pin - Fully Raised	110 in	2794 mm
	Dump angle at full height	40 °	40 °
	Overall Height to top of ROPS	76 in	1930 mm
	Overall length with bucket	121 in	3076 mm
	Overall Length without Bucket	93 in	2360 mm
	Specified Height	30 in	771 mm
	Reach at Specified Height	59 in	1494 mm
	Dump angle at specified height	75 °	75 °
	Carry Position	6 in	165 mm
	Maximum Rollback Angle at Carry Position	28 °	28 °
	Digging Position	0.71 in	18 mm
	Angle of Departure with STD Counterweight	28 °	28 °
	Ground clearance	8 in	213 mm
	Track gauge	45 in	1148 mm
	Track Shoe Width	12 in	300 mm
	Crawler base	46 in	1168 mm
	Overall width less bucket	57 in	1448 mm
	Bucket Width	60 in	1524 mm
	Clearance Radius - Front with Bucket	76 in	1918 mm
	Track Type / Track Rollers / Roller Type	Rubber / 4 / Steel	Rubber / 4 / Steel
Performances	Ground Speed - Single Speed	6 mph	10 km/h
	Drawbar Pull/Traction Effort	7161 lb	3248 kg
	Bucket Breakout - Tilt Cylinder	3501 lb	1588 kg
	Bucket Breakout - Lift Cylinder	3730 lb	1692 kg
Engine	Engine brand	Yanmar	Yanmar
	Engine model	4TNV88	4TNV88
	Motor Type	Radial Piston	Radial Piston
	Gross Power / Power	34.30 kW @ 2500 rpm	34.30 kW @ 2500 rpm
	Battery voltage	12 V	12 V
	Cold Cranking Amps at Temperature (CCA)	800 A	800 A
Hydraulics	Alternator - Voltage / Ampere	12 V / 100 A	12 V / 100 A
	Standard flow - Auxiliary hydraulics	17 US gpm	63.60 l/min
Tank capacities	Oil Pan Capacity	2 US gal	6.40 l
	Hydraulic tank capacity	9 US gal	34.80 l
	Fuel tank	16 US gal	59.40 l
	Displacement / Number of cylinders	0.58 US gal / 4	2.20 l / 4



STANDARD FEATURES

- Hour meter
- Anti-Vandalism Protection
- Auxiliary Hydraulics
- Swing-Out Cooler
- Hydraloc™ Safety System
- Lift Arm Support Device
- Back-Up Alarm
- ROPS/FOPS Level II Overhead Guard
- Horn
- Hand/Foot Controls
- High-Back Adjustable Seat
- All-Tach® Attachment Mounting System
- Operator Restraint Bar

OPTIONAL FEATURES

- Counterweight
- Power-A-Tach® Attachment Mounting System
- Sound reduction Package
- Suspension Seat - Mechanical
- Selectable Self-Leveling Hydraulic Lift Action
- Cab Enclosure
- Back-Up Alarm
- Engine Block Heater
- Suspension Seat - Air Ride
- Strobe Light
- Bluetooth car radio
- Rear camera with screen in cab
- Cabin with Heat and Air Conditioning

Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



One Gehl Way, West Bend, WI 53095  
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT