

RT135

COMPACT LOADERS



Key Features

- ✓ Compact Dimensions
- ✓ Pilot Joystick Controls
- ✓ IdealTrax™ Automatic Track Tensioning
- ✓ All-Tach™ Attachment System (Universal Type)
- ✓ ROPS/FOPS Level II

Key Specifications

- ✓ 1,350 lbs. (612 kg) Rated Operating Capacity (35%)
- ✓ 46.4 hp (35 kW) Yanmar Engine Stage 3A
- ✓ 110" (2794 mm) Height to Hinge Pin
- ✓ 57" (1448 mm) Overall Machine Width
- ✓ 76" (1930 mm) Overall Height

SPECIFICATIONS

		METRIC
Capacities	Operating Weight	2953 kg
	Operating Capacity at 35% Tipping Load	612.35 kg
	Operating Capacity At 50% Tipping Load	875 kg
	Tipping capacity	1750 kg
Weight and dimensions	Overall Operating Height - Fully Raised	3670 mm
	Height to Hinge Pin - Fully Raised	2794 mm
	Dump angle at full height	40 °
	Overall Height to top of ROPS	1930 mm
	Overall length with bucket	3076 mm
	Overall Length without Bucket	2360 mm
	Specified Height	771 mm
	Reach at Specified Height	1494 mm
	Dump angle at specified height	75 °
	Carry Position	165 mm
	Maximum Rollback Angle at Carry Position	28 °
	Digging Position	18 mm
	Angle of Departure with STD Counterweight	28 °
	Ground clearance	213 mm
	Track gauge	1148 mm
	Track Shoe Width	300 mm
	Crawler base	1168 mm
	Overall width less bucket	1448 mm
Performances	Bucket Width	1524 mm
	Clearance Radius - Front with Bucket	1918 mm
	Track Type / Track Rollers / Roller Type	Rubber / 4 / Steel
	Ground Speed - Single Speed	10 km/h
Engine	Drawbar Pull/Tractive Effort	3248 kg
	Bucket Breakout - Tilt Cylinder	1588 kg
	Bucket Breakout - Lift Cylinder	1692 kg
	Engine brand	Yanmar
	Engine model	4TNV88
	Motor Type	Radial Piston
	Gross Power / Power	34.30 kW @ 2500 rpm
Hydraulics	Battery voltage	12 V
	Cold Cranking Amps at Temperature (CCA)	800 A
	Alternator - Voltage / Ampere	12 V / 100 A
	Standard flow - Auxiliary hydraulics	63.60 l/min
Tank capacities	Oil Pan Capacity	6.40 l
	Hydraulic tank capacity	34.80 l
	Fuel tank	59.40 l
	Displacement / Number of cylinders	2.20 l / 4



STANDARD FEATURES

- Hour meter
- Anti-Vandalism Protection
- Auxiliary Hydraulics
- Swing-Out Cooler
- Hydraloc™ Safety System
- Lift Arm Support Device
- Back-Up Alarm
- ROPS/FOPS Level II Overhead Guard
- Horn
- Hand/Foot Controls
- High-Back Adjustable Seat
- All-Tach® Attachment Mounting System
- Operator Restraint Bar

OPTIONAL FEATURES

- Counterweight
- Power-A-Tach® Attachment Mounting System
- Sound reduction Package
- Suspension Seat - Mechanical
- Selectable Self-Leveling Hydraulic Lift Action
- Cab Enclosure
- Back-Up Alarm
- Engine Block Heater
- Suspension Seat - Air Ride
- Strobe Light
- Bluetooth car radio
- Rear camera with screen in cab
- Cabin with Heat and Air Conditioning

Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



One Gehl Way, West Bend, WI 53095
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT