## **TRACK LOADERS**



**GEHL**®

	kiiss cicated oii	May 8, 2024 at 4:31:24 a.m. l
Capacities		Metric
Operating Weight		2953 kg
Perating Capacity at 35% Tipping Load		612 kg
Perating Capacity At 50% Tipping Load		875 kg
ipping capacity		1750 kg
Veight and dimensions		
verall Operating Height - Fully Raised	h27	3670 mm
eight to Hinge Pin – Fully Raised	h28	2794 mm
ump angle at full height	a5	40 °
verall Height to top of ROPS	h17	1930 mm
verall length with bucket	l16	3076 mm
verall Length without Bucket	l1	2360 mm
pecified Height	h31	771 mm
each at Specified Height	r4	1494 mm
ump angle at specified height	a17	75 °
laximum Rollback Angle at Ground	a13	28 °
arry Position	d5	165 mm
naximum Rollback Angle at Carry Position	a14	28 °
igging Position	h32	18 mm
ngle of Departure with STD Counterweight		28 °
round clearance	m4	213 mm
rack gauge	b10	1148 mm
rack Shoe Width	b20	300 mm
rawler base	y2	1168 mm
verall width less bucket	b1	1448 mm
ucket Width	e1	1524 mm
learance Radius - Front with Bucket	b18	1918 mm
learance Circle - Rear	wa1	1440 mm
rack Type / Track Rollers / Roller Type		Rubber / 4 / Steel
erformances		
round Speed - Single Speed		10 km/h
Drawbar Pull/Tractive Effort		3248 kg
ucket Breakout - Tilt Cylinder		1588 kg
sucket Breakout - Lift Cylinder		1692 kg
ngine		
ngine brand		Yanmar
ngine model		4TNV88
Notor Type		Radial Piston
ross Power / Power		34.30 kW @ 2500 rpm
attery voltage		12 V
old Cranking Amps at Temperature (CCA)		800 A
Iternator - Voltage / Ampere		12 V / 100 A
lydraulics		,
tandard flow - Auxiliary hydraulics		63.60 l/min
ank capacities		05.00 (/IIIII
Dil Pan Capacity		6.40 l
lydraulic tank capacity		34.80 l
uel tank		59.40 l
isplacement / Number of cylinders		2.20 l / 4





Siège Social P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095 Tel: (262) 334-9461 - Fax: (262) 338-7517 www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend