


# RT165

# TRACK LOADERS



# GEHL®

Kapazität		Metrisch
Operating Weight		3638 kg
Operating Capacity at 35% Tipping Load		748.42 kg
Operating Capacity At 50% Tipping Load		1069 kg
Tipping capacity		2139 kg
Gewicht und Abmessungen		
Overall Operating Height - Fully Raised	h27	4008 mm
Höhe bis Schaufeldrehpunkt – bei max. Hubhöhe	h28	3038 mm
Reach - Fully Raised	dp1	641 mm
Auskippwinkel bei voller Hubhöhe	a5	39 °
Dump Height - Fully Raised	h29	2329 mm
Maximum Rollback Angle - Fully Raised	a4	98 °
Overall Height to top of ROPS	h17	1969 mm
Overall length with bucket	l16	3205 mm
Overall Length without Bucket	l1	2393 mm
Specified Height	h31	1638 mm
Reach at Specified Height	r4	559 mm
Dump angle at specified height	a17	70 °
Maximum Rollback Angle at Ground	a13	28 °
Carry Position	d5	198 mm
Maximum Rollback Angle at Carry Position	a14	28 °
Digging Position	h32	53 mm
Bodenfreiheit der Maschine	m4	185 mm
Track gauge	b10	1407 mm
Track Shoe Width	b20	400 mm
Crawler base	y2	1265 mm
Overall width less bucket	b1	1727 mm
Schaufelbreite	e1	1676 mm
Clearance Radius - Front with Bucket	b18	1979 mm
Clearance Circle - Rear	wa1	1440 mm
Track Type / Track Rollers / Roller Type		Rubber / 4 / Steel
Leistung		
Ground Speed - Single Speed		10.50 km/h
Drawbar Pull/Tractive Effort		4345 kg
Bucket Breakout - Tilt Cylinder		1919 kg
Bucket Breakout - Lift Cylinder		2295 kg
Motor		
Marke		Yanmar
Motor Modell		4TNV98C-NMS2V
Motor Type		Radial Piston
Gross Power / Power		51.70 kW @ 2500 rpm
Batterie		12 V
Cold Cranking Amps at Temperature (CCA)		950 A
Alternator - Voltage / Ampere		112 V / 100 A
Hydraulisch		
Zusatzhydraulik		71 l/min
High-Flow Auxiliary Hydraulics – Option		113 l/min
Tankkapazität		
Oil Pan Capacity		9 l
Kapazität des Hydraulikölbehälters		39 l
Kapazität des Kraftstoffbehälters		62.50 l
Hubraum / Anzahl der Zylinder		3.30 l / 4



# GEHL®

Siège Social  
P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095  
Tel: (262) 334-9461 - Fax: (262) 338-7517  
[www.gehl.com](http://www.gehl.com)



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend