RT165 COMPACT LOADERS






KEY FEATURES

- Multiple Track Widths and Tread Patterns
 Control Choices: T-Bar, Pilot Joystick and Hand/Foot
- ✓ IdealTrax™ Automatic Track Tensioning
- ✓ High-Flow Auxiliary Hydraulics Available
- ✓ Swing-Out Cooler

KEY SPECIFICATIONS

- 748 kg (1,650 lbs.) Rated Operating Capacity (35%)
 51.7 kW (69.3 hp) Yanmar Engine / 4TNV98C-NMS2V / Stage V
- √ 3038 mm (119.6") Height to Hinge Pin
- ✓ 1676 mm (66") Overall Machine Width
- ✓ 1969 mm (77.5") Overall Height

		METRIC
CAPACITIES	Operating Weight	3638 kg
	Operating Capacity at 35% Tipping Load	748.42 kg
	Operating Capacity At 50% Tipping Load	1069 kg
	Tipping capacity	2139 kg
WEIGHT AND DIMENSIONS	Overall Operating Height - Fully Raised	4008 mm
	Height to Hinge Pin - Fully Raised	3038 mm
	Reach - Fully Raised	641 mm
	Dump angle at full height	39 °
	Dump Height - Fully Raised	2329 mm
	Maximum Rollback Angle - Fully Raised	98 °
	Overall Height to top of ROPS	1969 mm
	Overall length with bucket	3205 mm
	Overall Length without Bucket	2393 mm
	Specified Height	1638 mm
	Reach at Specified Height	559 mm
	Dump angle at specified height	70 °
	Carry Position	198 mm
	Maximum Rollback Angle at Carry Position	28 °
	Digging Position	53 mm
	Ground clearance	185 mm
	Track gauge	1428 mm
	Track Shoe Width	400 mm
	Crawler base	1265 mm
	Overall width less bucket	1753 mm
	Bucket Width	1778 mm
	Clearance Radius - Front with Bucket	1979 mm
	Track Type / Track Rollers / Roller Type	Rubber / 4 / Steel
PERFORMANCES	Ground Speed - Single Speed	10.50 km/h
	Drawbar Pull/Tractive Effort	4345 kg
	Bucket Breakout - Tilt Cylinder	1919 kg
	Bucket Breakout - Lift Cylinder	2295 kg
ENGINE	Engine brand	Yanmar
	Engine model	4TNV98C-NMS2V
	Motor Type	Radial Piston
	Engine power (Hp)	74 Hp
	Engine power (kW)	51.70 kW
	Battery voltage	12 V
	Cold Cranking Amps at Temperature (CCA)	950 A
	Alternator - Voltage / Ampere	12 V / 100 A
HYDRAULICS	Standard flow - Auxiliary hydraulics	71 l/min
	High-Flow Auxiliary Hydraulics - Option	113 l/min
TANK CAPACITIES HYDRAULICS	Oil Pan Capacity	91
	Hydraulic tank capacity	391
	Fuel tank	62.50 I
	Number of cylinders	4





STANDARD FEATURES

- Auxiliary Hydraulics
- Lift Arm Support Device
- · Operator Restraint Bar
- Hour meter
- All-Tach® Attachment Mounting System
- High-Back Adjustable Seat
- Back-Up Alarm
- Anti-Vandalism Protection
- Swing-Out Cooler
- Horn
- Hand/Foot Controls
- ROPS/FOPS Level II Overhead Guard
- Hydraloc™ Safety System

OPTIONAL FEATURES

- Two-Speed Drive
- Pilot Joystick Controls
- High-Flow Auxiliary Hydraulics
- Air Conditioning
- Foot and Hand Throttles (Dual Joystick and T-bar)
- Suspension Seat Air Ride
- Back-Up Alarm
- Cab Enclosure
- Selectable Self-Leveling Hydraulic Lift Action
- Hydraglide™ Ride Control
- T-Bar Controls
- Suspension Seat Mechanical
- Power-A-Tach® Attachment Mounting System
- Engine Block Heater
- Heating in cab
- Counterweight