

RT215

COMPACT LOADERS

GEHL®



KEY FEATURES

- ✓ IdealTrax™ - Automatic Track Tensioning System
- ✓ Low Effort Joystick Pilot Controls
- ✓ Air Suspension Seat*
- ✓ Cab Enclosure with Heat and Air Conditioning*
- ✓ High Flow Auxiliary Hydraulics*
- ✓ 2 Travel Speeds
- ✓ Power-A-Tach Quick Coupler*
- ✓ Lift Arm Float Mode and Hydraglide™ Ride Control

KEY SPECIFICATIONS

- ✓ Operating capacity (35%) - 975 kg (2,150 lbs.)
- ✓ Overall height to top of ROPS - 2111 mm (83.1")
- ✓ 53.7 kW (72 hp) engine
- ✓ Yanmar / 4TNV98CT-XNMSLV / Stage V
- ✓ 294 Nm (217 ft.-lbs.) @ 1800 rpm max torque
- ✓ 29.5 kn (6631 lbf) tilt breakout force
- ✓ 3251 mm (128") height to hinge pin
- ✓ 1765 mm (69.5") machine width - less bucket
- ✓ 4491 kg (9,900 lbs.) operating weight

| | | METRIC |
|--|---|--|
| CAPACITIES | Operating Weight | 4490 kg |
| | Operating Capacity at 35% Tipping Load | 975 kg |
| | Operating Capacity At 50% Tipping Load | 1393 kg |
| | Tipping capacity | 2787 kg |
| WEIGHT AND DIMENSIONS | Overall Operating Height - Fully Raised | 4267 mm |
| | Height to Hinge Pin - Fully Raised | 3251 mm |
| | Reach - Fully Raised | 876 mm |
| | Dump angle at full height | 39 ° |
| | Dump Height - Fully Raised | 2489 mm |
| | Maximum Rollback Angle - Fully Raised | 102.50 ° |
| | Overall Height to top of ROPS | 2111 mm |
| | Overall length with bucket | 3769 mm |
| | Overall Length without Bucket | 2959 mm |
| | Specified Height | 1720 mm |
| | Reach at Specified Height | 795 mm |
| | Dump angle at specified height | 75 ° |
| | Carry Position | 208 mm |
| | Maximum Rollback Angle at Carry Position | 31.60 ° |
| | Digging Position | 16 mm |
| | Angle of Departure with STD Counterweight | 29.20 ° |
| | Ground clearance | 320 mm |
| | Track gauge | 1313 mm |
| | Track Shoe Width | 450 mm |
| | Crawler base | 1483 mm |
| Overall width less bucket | 1765 mm | |
| Bucket Width | 1877 mm | |
| Clearance Radius - Front with Bucket | 2403 mm | |
| Track Type / Track Rollers / Roller Type | Rubber / 5 / Steel | |
| PERFORMANCES | Ground Speed - Single Speed | 9.50 km/h |
| | Drawbar Pull/Traction Effort | 5503 kg |
| | Bucket Breakout - Tilt Cylinder | 3008 kg |
| | Bucket Breakout - Lift Cylinder | 2940 kg |
| ENGINE | Engine brand | Yanmar |
| | Engine model | 4TNV98CT-XNMSLV |
| | Motor Type | Axial Piston with planetary gear box reduction |
| | Engine power (Hp) | 72.82 Hp |
| | Engine power (kW) | 53.70 kW |
| | Battery voltage | 12 V |
| | Cold Cranking Amps at Temperature (CCA) | 850 A |
| Alternator - Voltage / Ampere | 14 V / 100 A | |
| HYDRAULICS | Standard flow - Auxiliary hydraulics | 82.50 l/min |
| TANK CAPACITIES | Hydraulic tank capacity | 52.20 l |
| | Fuel | 91 l |
| | Displacement / Number of cylinders | 3.30 l / 4 |



STANDARD FEATURES

- Anti-Vandalism Lock Provisions
- IdealTrax® automatic track tensioning system
- Back-Up Alarm
- Ceiling light
- Cup Holder
- Foot and Hand Throttles (Dual Joystick and T-bar)
- Front and Rear - Work Lights
- Hydraglide™ Ride Control
- Lockable Storage Box
- Maintenance Free Dual and Triple Flange Rollers Each Side
- Mechanical Lift Cylinder Lock
- Open Canopy w/ right side and rear glass
- Parking Brake
- Pilot Joystick Controls
- Proportional Auxiliary Hydraulics w/ Case Drain & Circuit Pressure Dump
- Selectable Self-Leveling Hydraulic Lift Action
- Tilt & Lift Arm Float Detent with Detent Disable
- Tilt-out Foot Pod
- Hydraloc™ Safety System

OPTIONAL FEATURES

- 3-inch Seatbelt
- Strobe Light
- Air Ride Suspension Seat
- Electronic Attachment Control - 14-Pin Connector
- Enclosed Cab with Heat and A/C
- IdealAccess™ Fold-Up Door
- Power-A-Tach® Attachment Mounting System
- Radio
- Rear view mirror
- Selectable Self-Leveling Hydraulic Lift Action
- Sliding Side Windows

GEHL Company reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. GEHL reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



One Gehl Way, West Bend, WI 53095
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT