

RT215

COMPACT LOADERS

GEHL®



KEY FEATURES

- ✓ IdealTrax™ - Automatic Track Tensioning System
- ✓ Low Effort Joystick Pilot Controls
- ✓ Air Suspension Seat*
- ✓ Cab Enclosure with Heat and Air Conditioning*
- ✓ High Flow Auxiliary Hydraulics*
- ✓ 2 Travel Speeds
- ✓ Power-A-Tach Quick Coupler*
- ✓ Lift Arm Float Mode and Hydraglide™ Ride Control

KEY SPECIFICATIONS

- ✓ Operating capacity (35%) - 975 kg (2,150 lbs.)
- ✓ Overall height to top of ROPS - 2111 mm (83.1")
- ✓ 53.7 kW (72 hp) engine
- ✓ Yanmar / 4TNV98CT-XNMSLV / Stage V
- ✓ 294 Nm (217 ft.-lbs.) @ 1800 rpm max torque
- ✓ 29.5 kn (6631 lbf.) tilt breakout force
- ✓ 3251 mm (128") height to hinge pin
- ✓ 1765 mm (69.5") machine width - less bucket
- ✓ 4491 kg (9,900 lbs.) operating weight

		METRIC
CAPACITIES	Operating Weight	4490 kg
	Operating Capacity at 35% Tipping Load	975 kg
	Operating Capacity At 50% Tipping Load	1393 kg
	Tipping capacity	2787 kg
WEIGHT AND DIMENSIONS	Overall Operating Height - Fully Raised	4267 mm
	Height to Hinge Pin - Fully Raised	3251 mm
	Reach - Fully Raised	876 mm
	Dump angle at full height	39 °
	Dump Height - Fully Raised	2489 mm
	Maximum Rollback Angle - Fully Raised	102.50 °
	Overall Height to top of ROPS	2111 mm
	Overall length with bucket	3769 mm
	Overall Length without Bucket	2959 mm
	Specified Height	1720 mm
	Reach at Specified Height	795 mm
	Dump angle at specified height	75 °
	Carry Position	208 mm
	Maximum Rollback Angle at Carry Position	31.60 °
	Digging Position	16 mm
	Angle of Departure with STD Counterweight	29.20 °
	Ground clearance	320 mm
	Track gauge	1313 mm
	Track Shoe Width	450 mm
	Crawler base	1483 mm
	Overall width less bucket	1765 mm
	Bucket Width	1877 mm
	Clearance Radius - Front with Bucket	2403 mm
	Track Type / Track Rollers / Roller Type	Rubber / 5 / Steel
PERFORMANCES	Ground Speed - Single Speed	9.50 km/h
	Drawbar Pull/Traction Effort	5503 kg
	Bucket Breakout - Tilt Cylinder	3008 kg
	Bucket Breakout - Lift Cylinder	2940 kg
ENGINE	Engine brand	Yanmar
	Engine model	4TNV98CT-XNMSLV
	Motor Type	Axial Piston with planetary gear box reduction
	Engine power (Hp)	72.82 Hp
	Engine power (kW)	53.70 kW
	Battery voltage	12 V
	Cold Cranking Amps at Temperature (CCA)	850 A
	Alternator - Voltage / Ampere	14 V / 100 A
HYDRAULICS	Standard flow - Auxiliary hydraulics	82.50 l/min
TANK CAPACITIES	Hydraulic tank capacity	52.20 l
	Fuel	91 l
	Displacement / Number of cylinders	3.30 l / 4

GEHL Company reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. GEHL reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



STANDARD FEATURES

- IdealTrax® automatic track tensioning system
- High-Back Adjustable Seat
- Foot and Hand Throttles (Dual Joystick and T-bar)
- Horn
- Tilt-out Foot Pod
- Operator Restraint Bar
- Selectable Self-Leveling Hydraulic Lift Action
- Turbo-Charged Engine
- Hydraloc™ Safety System
- Anti-Vandalism Lock Provisions
- Open Canopy w/ right side and rear glass
- Back-Up Alarm
- Lockable Storage Box
- Maintenance Free Dual and Triple Flange Rollers Each Side
- Hydraglide™ Ride Control
- ROPS/FOPS Level II Overhead Guard
- Pilot Joystick Controls
- All-Tach® Attachment Mounting System
- Proportional Auxiliary Hydraulics w/ Case Drain & Circuit Pressure Dump

OPTIONAL FEATURES

- Swing-out Cab Door
- Counterweight
- 3-inch Seatbelt
- Strobe Light
- Engine Block Heater
- Easy Manager
- Sliding Side Windows
- Rear camera with cab display screen
- Rear view mirror
- Sound Reduction Material
- Electronic Attachment Control - 14-Pin Connector



One Gehl Way, West Bend, WI 53095
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT