

RT215

COMPACT LOADERS



Key Features

- ✓ IdealTrax™ - Automatic Track Tensioning System
- ✓ Low Effort Joystick Pilot Controls
- ✓ Air Suspension Seat*
- ✓ Cab Enclosure with Heat and Air Conditioning*
- ✓ High Flow Auxiliary Hydraulics*
- ✓ 2 Travel Speeds
- ✓ Power-A-Tach Quick Coupler*
- ✓ Lift Arm Float Mode and Hydraglide™ Ride Control

Key Specifications

- ✓ Operating capacity (35%) - 975 kg (2,150 lbs.)
- ✓ Overall height to top of ROPS - 2111 mm (83.1")
- ✓ 53.7 kW (72 hp) engine
- ✓ Yanmar / 4TNV98CT-XNMSLV / Stage V
- ✓ 294 Nm (217 ft.-lbs.) @ 1800 rpm max torque
- ✓ 29.5 kn (6631 lbf.) tilt breakout force
- ✓ 3251 mm (128") height to hinge pin
- ✓ 1765 mm (69.5") machine width - less bucket
- ✓ 4491 kg (9,900 lbs.) operating weight

SPECIFICATIONS

| | | IMPERIAL |
|-----------------------|---|--|
| Capacities | Operating Weight | 9899 lb |
| | Operating Capacity at 35% Tipping Load | 2150 lb |
| | Operating Capacity At 50% Tipping Load | 3071 lb |
| | Tipping capacity | 6144 lb |
| Weight and dimensions | Overall Operating Height - Fully Raised | 168 in |
| | Height to Hinge Pin - Fully Raised | 128 in |
| | Reach - Fully Raised | 34 in |
| | Dump angle at full height | 39 ° |
| | Dump Height - Fully Raised | 98 in |
| | Maximum Rollback Angle - Fully Raised | 102.50 ° |
| | Overall Height to top of ROPS | 83 in |
| | Overall length with bucket | 148 in |
| | Overall Length without Bucket | 116 in |
| | Specified Height | 68 in |
| | Reach at Specified Height | 31 in |
| | Dump angle at specified height | 75 ° |
| | Carry Position | 8 in |
| | Maximum Rollback Angle at Carry Position | 31.60 ° |
| | Digging Position | 0.63 in |
| | Angle of Departure with STD Counterweight | 29.20 ° |
| | Ground clearance | 13 in |
| | Track gauge | 52 in |
| | Track Shoe Width | 18 in |
| | Crawler base | 58 in |
| | Overall width less bucket | 69 in |
| | Bucket Width | 74 in |
| | Clearance Radius - Front with Bucket | 95 in |
| | Track Type / Track Rollers / Roller Type | Rubber / 5 / Steel |
| Performances | Ground Speed - Single Speed | 6 mph |
| | Drawbar Pull/Traction Effort | 12132 lb |
| | Bucket Breakout - Tilt Cylinder | 6632 lb |
| | Bucket Breakout - Lift Cylinder | 6482 lb |
| Engine | Engine brand | Yanmar |
| | Engine model | 4TNV98CT-XNMSLV |
| | Motor Type | Axial Piston with planetary gear box reduction |
| | Gross Power / Power | 53.70 kW @ 2500 rpm |
| | Battery voltage | 12 V |
| | Cold Cranking Amps at Temperature (CCA) | 850 A |
| | Alternator - Voltage / Ampere | 14 V / 100 A |
| Hydraulics | Standard flow - Auxiliary hydraulics | 22 US gpm |
| Tank capacities | Hydraulic tank capacity | 14 US gal |
| | Fuel tank | 24 US gal |
| | Displacement / Number of cylinders | 0.87 US gal / 4 |



STANDARD FEATURES

- Proportional Auxiliary Hydraulics w/ Case Drain & Circuit Pressure Dump
- Tilt & Lift Arm Float Detent with Detent Disable
- Turbo-Charged Engine
- Ceiling light
- Hydraloc™ Safety System
- Maintenance Free Dual and Triple Flange Rollers Each Side
- Selectable Self-Leveling Hydraulic Lift Action
- Tilt-out Foot Pod
- Back-Up Alarm
- Two-Speed Drive
- Anti-Vandalism Lock Provisions
- ROPS/FOPS Level II Overhead Guard
- Lockable Storage Box
- Front and Rear - Work Lights
- Horn
- Cup Holder
- Hydraglide™ Ride Control
- High-Back Adjustable Seat
- Foot and Hand Throttles (Dual Joystick and T-bar)

OPTIONAL FEATURES

- Electronic Attachment Control - 14-Pin Connector
- Sound Reduction Material
- Power-A-Tach® Attachment Mounting System
- Selectable Self-Leveling Hydraulic Lift Action
- Engine Block Heater
- Rear view mirror
- IdealAccess™ Fold-Up Door
- Enclosed Cab with Heat and A/C
- Rear camera with cab display screen
- Strobe Light
- 3-inch Seatbelt

Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



One Gehl Way, West Bend, WI 53095
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT