

# R105

## COMPACT LOADERS

**GEHL**®



### KEY FEATURES

- ✓ All-Tach® Attachment System (Universal-Type)
- ✓ Hydraloc™ System
- ✓ ROPS/FOPS Level II
- ✓ Dual T-Bar Control System
- ✓ Audible Back-Up Alarm
- ✓ Standard High Back Cushion Seat

### KEY SPECIFICATIONS

- ✓ Operating capacity (50%) - 476 kg (1,050 lbs.)
- ✓ Overall height to top of ROPS - 1786 mm (70.3")
- ✓ Gross Power - 25.5 kW (34.7 hp) @ 2800 rpm
- ✓ Yanmar / 3TNV88C-KMSV / Stage V
- ✓ 109.4 Nm (80.7 ft.-lbs.) @ 1820 rpm max torque
- ✓ 2731 mm (107.5") height to hinge pin
- ✓ 1232 mm (48.5") machine width - less bucket
- ✓ 1905 kg (4,200 lbs.) operating weight

		METRIC
CAPACITIES	Operating Capacity At 50% Tipping Load	476.27 kg
	Rated Operating Capacity with Optional Counterweight	533 kg
	Operating Weight	1905 kg
	Unladen weight	1678 kg
	Tipping capacity	952.54 kg
WEIGHT AND DIMENSIONS	Wheelbase	876 mm
	Overall Operating Height - Fully Raised	3607 mm
	Height to Hinge Pin - Fully Raised	2731 mm
	Overall Height to top of ROPS	1784 mm
	Dump angle at full height	40 °
	Dump height	2083 mm
	Overall length with bucket	2997 mm
	Dump reach - Full height	641 mm
	Rollback at ground	31 °
	Seat to ground height	826 mm
	Overall width less bucket	1224 mm
	Bucket Width	1372 mm
	Ground clearance	159 mm
	Overall length - Less Bucket	2248 mm
	Clearance Radius - Front with Bucket	1829 mm
	Rear departure angle	22 °
PERFORMANCES	Travel speed (unladen)	8.26 km/h
WHEELS	Standard tires	27 x 8.5 x 15 HD
ENGINE	Engine brand	Yanmar
	Engine model	3TNV88C-KMSV
	Engine nom	Stage V, Tier 4
	Max. torque / Engine rotation	109.40 Nm / 1820 rpm
	Power source	Diesel
	Engine power (Hp / kW)	34 Hp / 25.50 kW
	Battery voltage	12 V
	Starter	2.30 kW
HYDRAULICS	Standard flow - Auxiliary hydraulics	55 l/min
TANK CAPACITIES	Fuel	36 l
	Hydraulic tank capacity	30.30 l
NOISE AND VIBRATION	Noise to environment (LwA)	101 dB
	Whole-Body Vibration (ISO 2631-1)	1.12 m/s <sup>2</sup>
	Vibration on hands/arms	< 1.70 m/s <sup>2</sup>

GEHL Company reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. GEHL reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



## STANDARD FEATURES

- T-Bar Controls
- Hydraloc™ Safety System
- Integral Access Plate (removable)
- High-Back Adjustable Seat
- Front and Rear - Work Lights
- Hour meter
- Hand/Foot Controls
- 12Volt Power Port
- Adjustable 2-inch Seat Belt
- Operator Restraint Bar
- Back-Up Alarm
- Servo-Controlled Hydrostatic Drive
- Lift Arm Support Device
- Anti-Vandalism Lock Provisions
- Battery charge indicator lamp
- All-Tach® Attachment Mounting System

## OPTIONAL FEATURES

- 3-inch Seatbelt
- Easy Manager
- Selectable Self-Leveling Hydraulic Lift Action 4
- Air suspension seat
- Radio
- Swing-out Cab Door
- Battery Disconnect
- Automatic engine shutdown
- Rotating Beacon
- Heat & Defrost
- Rear view mirror
- Simplified lift system
- Engine Block Heater
- Counterweight



One Gehl Way, West Bend, WI 53095  
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT