

R134

COMPACT LOADERS



Key Features

- ✓ PowerView® Boom Lift Arm - Radial
- ✓ Hydraloc™ System
- ✓ ROPS/FOPS
- ✓ Dual T-Bar
- ✓ Cushion Seat
- ✓ Battery Charge Indicator Lamp
- ✓ Hourmeter
- ✓ Vandalism Lock Provisions - Fuel and Engine Cover

Key Specifications

- ✓ Operating capacity (50%) - 612 kg (1,340 lbs.)
- ✓ Overall height to top of ROPS - 1826 mm (71.9")
- ✓ Gross Power - 36.4 kW (48.8 hp) @ 2600 rpm
- ✓ Yanmar / 4TNV88 / Stage 3A
- ✓ 142 Nm (105 ft.-lbs.) @ 1600 rpm max torque
- ✓ 2794 mm (110") height to hinge pin
- ✓ 1346 mm (53") machine width - less bucket
- ✓ 2087 kg (4,601 lbs.) operating weight

SPECIFICATIONS

		IMPERIAL	METRIC
Capacities	Rated Operating Capacity	1349 lb	612 kg
	Unladen weight	4850 lb	2200 kg
	Tipping capacity	2698 lb	1224 kg
Weight and dimensions	Wheelbase	36 in	923 mm
	Overall Operating Height - Fully Raised	141 in	3584 mm
	Height to Hinge Pin - Fully Raised	110 in	2794 mm
	Overall Height to top of ROPS	72 in	1826 mm
	Dump angle at full height	42 °	42 °
	Dump height	86 in	2197 mm
	Overall length with bucket	116 in	2952 mm
	Dump reach - Full height	21 in	528 mm
	Rollback at ground	29 °	29 °
	Rollback Angle at Full Height	99 °	99 °
	Seat to ground height	34 in	853 mm
	Overall width less bucket	53 in	1346 mm
	Bucket Width	61 in	1562 mm
	Ground clearance	8 in	211 mm
	Overall length - Less Bucket	91 in	2314 mm
	Clearance Radius - Front with Bucket	69 in	1758 mm
	Rear departure angle	29 °	29 °
Performances	Travel speed (unladen)	7 mph	10.70 km/h
Wheels	Transmission type	Hydrostatic	Hydrostatic
	Standard tires	10 x 16.5 - 10 PR HD	10 x 16.5 - 10 PR HD
Engine	Engine brand	Yanmar	Yanmar
	Engine model	4TNV88	4TNV88
	Engine norm	Stage IIIA	Stage IIIA
	Gross Power	48.80 Hp	48.80 Hp
	Max. torque / Engine rotation	103 ft/lbs / 1600 rpm	140 Nm / 1600 rpm
	Power source	Diesel	Diesel
	Number of cylinders	4	4
	Battery voltage	12 V	12 V
	Accessory plug	12 V	12 V
	Alternator - Ampere	55 A	55 A
	Starter	3 kW	3 kW
Hydraulics	Standard flow - Auxiliary hydraulics	17 US gpm	63.40 l/min
	Auxiliary Hydraulic Pressure	2756 PSI	190 bar
Tank capacities	Fuel tank	12 US gal	47 l
	Hydraulic tank capacity	8 US gal	30 l
	Displacement	0.58 US gal	2.20 l
	LH Chain case	2 US gal	8.30 l
	RH Chain case	2 US gal	8.30 l



STANDARD FEATURES

- Hour meter
- T-Bar Controls
- High-Back Adjustable Seat
- Battery charge indicator lamp
- Adjustable 2-inch Seat Belt
- Hydraloc™ Safety System
- Operator Restraint Bar
- Lift Arm Support Device
- Back-Up Alarm
- Anti-Vandalism Lock Provisions
- ROPS/FOPS Level II Overhead Guard
- Front and Rear - Work Lights
- 12Volt Power Port
- Hand/Foot Controls
- Integral Access Plate (removable)
- All-Tach® Attachment Mounting System

OPTIONAL FEATURES

- Selectable Self-Leveling Hydraulic Lift Action 4
- Rotating Beacon
- Simplified lift system
- Engine Block Heater
- Horn
- Rear view mirror
- Heat & Defrost
- 3-inch Seatbelt
- Automatic engine shutdown
- Swing-out Cab Door
- Radio
- Easy Manager
- Battery Disconnect
- Air suspension seat

Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



One Gehl Way, West Bend, WI 53095
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT