

R220

COMPACT LOADERS

GEHL®



KEY FEATURES

- ✓ All-Tach® Attachment System (Universal-Type)
- ✓ Hydraloc™ System
- ✓ ROPS/FOPS Level II
- ✓ Dual T-Bar, Hand/Foot or Joystick Control System
- ✓ Zero Maintenance Axles w/8-Bolt Rims
- ✓ Acoustical Sound Material and Deluxe Headliner
- ✓ Standard High Back Cushion Seat

KEY SPECIFICATIONS

- ✓ Operating Capacity (50%) - 998 kg (2,200 lbs.)
- ✓ Overall height to top of ROPS - 2057 mm (81")
- ✓ Gross Power - 53.7 kW (72 hp) @ 2500 rpm
- ✓ Yanmar / 4TNV98C-NMSLV / Stage V
- ✓ 294 Nm (217 ft.-lbs.) @ 1625 rpm max torque
- ✓ 3124 mm (123") height to hinge pin
- ✓ 1712 mm (67.4") machine width - less bucket
- ✓ 3620 kg (7,980 lbs.) operating weight

		METRIC	IMPERIAL
CAPACITIES	Rated Operating Capacity	998 kg	2200 lb
	Rated Operating Capacity with Optional Counterweight	1075 kg	2370 lb
	Unladen weight	3620 kg	7981 lb
WEIGHT AND DIMENSIONS	Wheelbase	1092 mm	43 in
	Overall Operating Height - Fully Raised	4089 mm	161 in
	Height to Hinge Pin - Fully Raised	3124 mm	123 in
	Overall Height to top of ROPS	2057 mm	81 in
	Dump angle at full height	40 °	
	Dump height	2388 mm	94 in
	Overall length with bucket	3467 mm	136 in
	Dump reach - Full height	685.80 mm	27 in
	Rollback at ground	28 °	
	Seat to ground height	1016 mm	40 in
	Overall width less bucket	1711.96 mm	67 in
	Bucket Width	1711.96 mm	67 in
	Ground clearance	203 mm	8 in
	Overall length - Less Bucket	2667 mm	105 in
PERFORMANCES	Clearance Radius - Front with Bucket	2223 mm	88 in
	Rear departure angle	25 °	
WHEELS	Travel speed (unladen)	12.90 km/h	8 mph
	Travel Speed with Two-Speed Option - Maximum	19.20 km/h	12 mph
ENGINE	Standard tires	12.00 x 16.5 HD	
	Engine brand	Yanmar	
	Engine model	4TNV98CT-NMSLV	
	Engine nom	Stage V	
	Max. torque / Engine rotation	294 Nm / 1625 rpm	217 ft/lbs / 1625 rpm
	Power source	Diesel	
	Engine power (Hp / kW)	72 Hp / 52.70 kW	
	Battery voltage	12 V	
HYDRAULICS	Starter	3 kW	
	Standard flow - Auxiliary hydraulics	90 l/min	24 US gpm
TANK CAPACITIES	High-Flow Auxiliary Hydraulics - Option	132.50 l/min	35 US gpm
	Fuel	68.10 l	18 US gal
	Hydraulic tank capacity	30.30 l	8 US gal
NOISE AND VIBRATION	Displacement	3.30 l	0.87 US gal
	Noise to environment (LwA)	101 dB	
	Whole-Body Vibration (ISO 2631-1)	0.96 m/s²	3 ft/s²
	Vibration on hands/arms	1.50 m/s²	5 ft/s²



STANDARD FEATURES

- Servo-Controlled Hydrostatic Drive
- ROPS/FOPS Level II Overhead Guard
- All-Tach® Attachment Mounting System
- Pilot Joystick Controls
- Hydraloc™ Safety System
- Lift Arm Support Device
- Integral Access Plate (removable)
- 12Volt Power Port
- High-Back Adjustable Seat
- Anti-Vandalism Lock Provisions
- Back-Up Alarm
- Operator Restraint Bar
- T-Bar Controls
- Horn
- Hour meter

OPTIONAL FEATURES

- Back-Up Alarm
- Radio
- Swing-out Cab Door
- Engine Block Heater
- LED Work Lights
- Rotating Beacon
- Selectable Self-Leveling Hydraulic Lift Action 4
- Automatic engine shutdown
- Battery Disconnect
- 3-inch Seatbelt
- Power-A-Tach® Attachment Mounting System
- Easy Manager
- Air suspension seat
- Rear view mirror
- Heat & Defrost

GEHL Company reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. GEHL reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



One Gehl Way, West Bend, WI 53095
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT