

R260

COMPACT LOADERS



Key Features

- ✓ All-Tach® Attachment System (Universal-Type)
- ✓ Hydraloc™ System
- ✓ ROPS/FOPS Level II
- ✓ Dual T-Bar, Hand/Foot or Joystick Control System
- ✓ Zero Maintenance Axles w/8-Bolt Rims
- ✓ Acoustical Sound Material and Deluxe Headliner
- ✓ Standard High Back Cushion Seat

Key Specifications

- ✓ Operating Capacity (50%) - 1179 kg (2,600 lbs.)
- ✓ Overall height to top of ROPS - 2057 mm (81")
- ✓ Gross Power - 53.7 kW (72 hp) @ 2500 rpm
- ✓ Yanmar / 4TNV98C-NMSLV / Stage V
- ✓ 294 Nm (217 ft.-lbs.) @ 1625 rpm max torque
- ✓ 3124 mm (123") height to hinge pin
- ✓ 1712 mm (67.4") machine width - less bucket
- ✓ 3719 kg (8,200 lbs.) operating weight

SPECIFICATIONS

		IMPERIAL	METRIC
Capacities	Rated Operating Capacity	2599 lb	1179 kg
	Rated Operating Capacity with Optional Counterweight	2780 lb	1261 kg
	Unladen weight	8199 lb	3719 kg
Weight and dimensions	Wheelbase	49 in	1257 mm
	Overall Operating Height - Fully Raised	161 in	4089 mm
	Height to Hinge Pin - Fully Raised	123 in	3124 mm
	Overall Height to top of ROPS	81 in	2057 mm
	Dump angle at full height	40 °	40 °
	Dump height	94 in	2388 mm
	Overall length with bucket	143 in	3632 mm
	Dump reach - Full height	27 in	686 mm
	Rollback at ground	28 °	28 °
	Seat to ground height	40 in	1016 mm
	Overall width less bucket	67 in	1711.96 mm
	Bucket Width	67 in	1711.96 mm
	Ground clearance	8 in	203 mm
	Overall length - Less Bucket	111 in	2832 mm
	Clearance Radius - Front with Bucket	90 in	2286 mm
Performances	Travel speed (unladen)	8 mph	12.90 km/h
	Travel Speed with Two-Speed Option - Maximum	12 mph	19.20 km/h
Wheels	Standard tires	12.00 x 16.5 HD	12.00 x 16.5 HD
Engine	Engine brand	Yanmar	Yanmar
	Engine model	4TNV98CT-NMSLV	4TNV98CT-NMSLV
	Engine norm	Stage V	Stage V
	Gross Power	53.70 kW	53.70 kW
	Net Power	52.70 kW	52.70 kW
	Max. torque / Engine rotation	217 ft/lbs / 1625 rpm	294 Nm / 1625 rpm
	Power source	Diesel	Diesel
	I.C. Engine power rating	53.70 Hp	53.70 Hp
	Battery voltage	12 V	12 V
	Starter	3 kW	3 kW
Hydraulics	Standard flow - Auxiliary hydraulics	24 US gpm	90 l/min
	High-Flow Auxiliary Hydraulics - Option	35 US gpm	132.50 l/min
Tank capacities	Fuel tank	22 US gal	81.40 l
	Hydraulic tank capacity	8 US gal	30.30 l
	Displacement	0.87 US gal	3.30 l
Noise and vibration	Noise to environment (LwA)	101 dB	101 dB
	Whole-Body Vibration (ISO 2631-1)	0.96 m/s²	0.96 m/s²
	Vibration on hands/arms	< 1.50 m/s²	< 1.50 m/s²



STANDARD FEATURES

- Hour meter
- T-Bar Controls
- High-Back Adjustable Seat
- Battery charge indicator lamp
- Adjustable 2-inch Seat Belt
- Hydraloc™ Safety System
- Operator Restraint Bar
- Lift Arm Support Device
- Anti-Vandalism Lock Provisions
- ROPS/FOPS Level II Overhead Guard
- Front and Rear - Work Lights
- 12Volt Power Port
- Horn
- Hand/Foot Controls
- Integral Access Plate (removable)

OPTIONAL FEATURES

- Selectable Self-Leveling Hydraulic Lift Action 4
- Power-A-Tach® Attachment Mounting System
- Back-Up Alarm
- Rotating Beacon
- Simplified lift system
- Engine Block Heater
- LED Work Lights
- Rear view mirror
- Heat & Defrost
- Hydraglide™ Ride Control
- 3-inch Seatbelt
- Automatic engine shutdown
- Swing-out Cab Door
- Radio
- Easy Manager

Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



One Gehl Way, West Bend, WI 53095
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT