


R260

SKID LOADERS



GEHL®

Kapazität		Metrisch	Zoll
Rated Operating Capacity		1179 kg	2599 lb
Rated Operating Capacity with Optional Counterweight		1261 kg	2780 lb
Eigengewicht		3719 kg	8199 lb
Gewicht und Abmessungen			
Overall Operating Height - Fully Raised	h27	4089 mm	161 in
Höhe bis Schaufeldrehpunkt – bei max. Hubhöhe	h28	3124 mm	123 in
Overall Height to top of ROPS	h17	2057 mm	81 in
Auskippwinkel bei voller Hubhöhe	a5	40 °	40 °
Dump height	h29	2388 mm	94 in
Overall length with bucket	l16	3632 mm	143 in
Dump reach - Full height	r6	686 mm	27 in
Einkippwinkel auf Standebene	a13	28 °	28 °
Seat to ground height	h30	1016 mm	40 in
Radstand	y	1257 mm	49 in
Overall width less bucket	b1	1711.96 mm	67 in
Schaufelbreite	e1	1711.96 mm	67 in
Bodenfreiheit der Maschine	m4	203 mm	8 in
Overall length - Less Bucket	l2	2832 mm	111 in
Clearance Radius - Front with Bucket	b18	2286 mm	90 in
Wendekreis - vorne ohne Schaufel	b19	1422 mm	56 in
Clearance Circle - Rear	wa1	1626 mm	64 in
Leistung			
Travel Speed with Two-Speed Option - Maximum		19.20 km/h	12 mph
Fahrtgeschwindigkeit (unbeladen)		12.90 km/h	8 mph
Reifen			
Standard tires		12.00x16.5 HD	12.00x16.5 HD
Motor			
Marke		Yanmar	Yanmar
Motor Modell		4TNV98CT-NMSLV	4TNV98CT-NMSLV
Motornorm		Stage V	Stage V
Gross Power		53.70 kW	53.70 kW
Net Power		52.70 kW	52.70 kW
Max. Drehmoment / Motordrehzahl		294 Nm / 1625 rpm	217 ft/lbs / 1625 rpm
Antriebsart		Diesel	Diesel
Nennleistung Verbrennungsmotor		53.70 Hp	53.70 Hp
Batterie		12 V	12 V
Starter		3 kW	3 kW
Hydraulisch			
Zusatzhydraulik		90 l/min	24 US gpm
High-Flow Auxiliary Hydraulics – Option		132.50 l/min	35 US gpm
Tankkapazität			
Kapazität des Kraftstoffbehälters		81.40 l	22 US gal
Reservoir Capacity Hydraulics		30.30 l	8 US gal
Hubraum		3.30 l	0.87 US gal
Lärm und Vibrationen			
Umgebungsgeräusch (LwA)		101 dB	101 dB
Ganzkörper Schwingungen (ISO 2631 - 1)		0.96 m/s²	0.96 m/s²
Vibrationswert an Händen/Armen		< 1.50 m/s²	< 1.50 m/s²



GEHL®

Siège Social
P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095
Tel: (262) 334-9461 - Fax: (262) 338-7517
www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend