

# R260

## COMPACT LOADERS



### Key Features

- ✓ All-Tach® Attachment System (Universal-Type)
- ✓ Hydraloc™ System
- ✓ ROPS/FOPS Level II
- ✓ Dual T-Bar, Hand/Foot or Joystick Control System
- ✓ Zero Maintenance Axles w/8-Bolt Rims
- ✓ Acoustical Sound Material and Deluxe Headliner
- ✓ Standard High Back Cushion Seat

### Key Specifications

- ✓ Operating Capacity (50%) - 1179 kg (2,600 lbs.)
- ✓ Overall height to top of ROPS - 2057 mm (81")
- ✓ Gross Power - 53.7 kW (72 hp) @ 2500 rpm
- ✓ Yanmar / 4TNV98C-NMSLV / Stage V
- ✓ 294 Nm (217 ft.-lbs.) @ 1625 rpm max torque
- ✓ 3124 mm (123") height to hinge pin
- ✓ 1712 mm (67.4") machine width - less bucket
- ✓ 3719 kg (8,200 lbs.) operating weight

## SPECIFICATIONS

|                       |  | IMPERIAL                | METRIC                  |
|-----------------------|--|-------------------------|-------------------------|
| Capacities            | Rated Operating Capacity                             | 2599 lb                 | 1179 kg                 |
|                       | Rated Operating Capacity with Optional Counterweight | 2780 lb                 | 1261 kg                 |
|                       | Unladen weight                                       | 8199 lb                 | 3719 kg                 |
| Weight and dimensions | Wheelbase  | 49 in                   | 1257 mm                 |
|                       | Overall Operating Height - Fully Raised              | 161 in                  | 4089 mm                 |
|                       | Height to Hinge Pin - Fully Raised                   | 123 in                  | 3124 mm                 |
|                       | Overall Height to top of ROPS                        | 81 in                   | 2057 mm                 |
|                       | Dump angle at full height                            | 40 °                    | 40 °                    |
|                       | Dump height  | 94 in                   | 2388 mm                 |
|                       | Overall length with bucket                           | 143 in                  | 3632 mm                 |
|                       | Dump reach - Full height                             | 27 in                   | 686 mm                  |
|                       | Rollback at ground                                   | 28 °                    | 28 °                    |
|                       | Seat to ground height                                | 40 in                   | 1016 mm                 |
|                       | Overall width less bucket                            | 67 in                   | 1711.96 mm              |
|                       | Bucket Width   | 67 in                   | 1711.96 mm              |
|                       | Ground clearance                                     | 8 in                    | 203 mm                  |
|                       | Overall length - Less Bucket                         | 111 in                  | 2832 mm                 |
|                       | Clearance Radius - Front with Bucket                 | 90 in                   | 2286 mm                 |
| Rear departure angle  | 25 °   | 25 °                    |                         |
| Performances          | Travel speed (unladen)                               | 8 mph                   | 12.90 km/h              |
|                       | Travel Speed with Two-Speed Option - Maximum         | 12 mph                  | 19.20 km/h              |
| Wheels                | Standard tires                                       | 12.00 x 16.5 HD         | 12.00 x 16.5 HD         |
| Engine                | Engine brand   | Yanmar                  | Yanmar                  |
|                       | Engine model   | 4TNV98CT-NMSLV          | 4TNV98CT-NMSLV          |
|                       | Engine norm  | Stage V                 | Stage V                 |
|                       | Gross Power  | 53.70 kW                | 53.70 kW                |
|                       | Net Power  | 52.70 kW                | 52.70 kW                |
|                       | Max. torque / Engine rotation                        | 217 ft/lbs / 1625 rpm   | 294 Nm / 1625 rpm       |
|                       | Power source   | Diesel                  | Diesel                  |
|                       | I.C. Engine power rating                             | 53.70 Hp                | 53.70 Hp                |
|                       | Battery voltage                                      | 12 V                    | 12 V                    |
|                       | Starter  | 3 kW                    | 3 kW                    |
| Hydraulics            | Standard flow - Auxiliary hydraulics                 | 24 US gpm               | 90 l/min                |
|                       | High-Flow Auxiliary Hydraulics - Option              | 35 US gpm               | 132.50 l/min            |
| Tank capacities       | Fuel tank  | 22 US gal               | 81.40 l                 |
|                       | Hydraulic tank capacity                              | 8 US gal                | 30.30 l                 |
|                       | Displacement   | 0.87 US gal             | 3.30 l                  |
| Noise and vibration   | Noise to environment (LwA)                           | 101 dB                  | 101 dB                  |
|                       | Whole-Body Vibration (ISO 2631-1)                    | 0.96 m/s <sup>2</sup>   | 0.96 m/s <sup>2</sup>   |
|                       | Vibration on hands/arms                              | < 1.50 m/s <sup>2</sup> | < 1.50 m/s <sup>2</sup> |



## STANDARD FEATURES

- Hour meter
- T-Bar Controls
- High-Back Adjustable Seat
- Battery charge indicator lamp
- Adjustable 2-inch Seat Belt
- Hydraloc™ Safety System
- Operator Restraint Bar
- Lift Arm Support Device
- Anti-Vandalism Lock Provisions
- ROPS/FOPS Level II Overhead Guard
- Front and Rear - Work Lights
- 12Volt Power Port
- Horn
- Hand/Foot Controls
- Integral Access Plate (removable)

## OPTIONAL FEATURES

- Selectable Self-Leveling Hydraulic Lift Action 4
- Power-A-Tach® Attachment Mounting System
- Back-Up Alarm
- Rotating Beacon
- Simplified lift system
- Engine Block Heater
- LED Work Lights
- Rear view mirror
- Heat & Defrost
- Hydraglide™ Ride Control
- 3-inch Seatbelt
- Automatic engine shutdown
- Swing-out Cab Door
- Radio
- Easy Manager

Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



One Gehl Way, West Bend, WI 53095  
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT