

**R260**

**SKID LOADERS**



**GEHL®**

Capacities		Imperial
Rated Operating Capacity		2599 lb
Rated Operating Capacity with Optional Counterweight		2780 lb
Unladen weight		8199 lb
Weight and dimensions		
Overall Operating Height - Fully Raised	h27	161 in
Height to Hinge Pin - Fully Raised	h28	123 in
Overall Height to top of ROPS	h17	81 in
Dump angle at full height	a5	40 °
Dump height	h29	94 in
Overall length with bucket	l16	143 in
Dump reach - Full height	r6	27 in
Rollback at ground	a13	28 °
Seat to ground height	h30	40 in
Wheelbase	y	49 in
Overall width less bucket	b1	67 in
Bucket Width	e1	67 in
Ground clearance	m4	8 in
Overall length - Less Bucket	l2	111 in
Clearance Radius - Front with Bucket	b18	90 in
Clearance Circle - Front without Bucket	b19	56 in
Clearance Circle - Rear	wa1	64 in
Performances		
Travel Speed with Two-Speed Option - Maximum		12 mph
Travel speed (unladen)		8 mph
Wheels		
Standard tires		12.00x16.5 HD
Engine		
Engine brand		Yanmar
Engine model		4TNV98CT-NMSLV
Engine norm		Stage V
Gross Power		53.70 kW
Net Power		52.70 kW
Max. torque / Engine rotation		217 ft/lbs / 1625 rpm
Power source		Diesel
I.C. Engine power rating		53.70 Hp
Battery voltage		12 V
Starter		3 kW
Hydraulics		
Standard flow - Auxiliary hydraulics		24 US gpm
High-Flow Auxiliary Hydraulics - Option		35 US gpm
Tank capacities		
Fuel tank		22 US gal
Reservoir Capacity Hydraulics		8 US gal
Displacement		0.87 US gal
Noise and vibration		
Noise to environment (LwA)		101 dB
Whole-Body Vibration (ISO 2631-1)		0.96 m/s <sup>2</sup>
Vibration to whole hand/arm		< 1.50 m/s <sup>2</sup>



# GEHL®

Siège Social  
P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095  
Tel: (262) 334-9461 - Fax: (262) 338-7517  
[www.gehl.com](http://www.gehl.com)



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend