

Technical sheet :


MT-X 1840 A



 **MANITOU**
HANDLING YOUR WORLD


Capacities		Metric	
Max. capacity		4000 kg	
Max. lifting height		17.55 m	
Maximum outreach		9.60 m	
Breakout force with bucket		8400 daN	
Weight and dimensions			
Overall length to carriage	I11	6.16 m	
Length to face of forks	I2	6.27 m	
Overall width	b1	2.42 m	
Overall height	h17	2.45 m	
Wheelbase	y	3.07 m	
Ground clearance	m4	0.37 m	
Overall cab width	b4	0.89 m	
Tilt-up angle	a4	12 °	
Tilt-down angle	a5	114 °	
External turning radius (over tyres)	Wa1	3.94 m	
Overall weight		12560 kg	
Unladen weight (with man basket)		12560 kg	
Tires type		Pneumatic	
Standard tires		Alliance 400/80 - 24 - 162A8	
Forks length / width / section	I / e / s	1200 mm x 125 mm x 50 mm	
Performances			
Lifting		18 s	
Lowering		14.40 s	
Extension		17.90 s	
Retraction		16.50 s	
Crowd		5.10 s	
Dump		4 s	
Engine			
Engine brand		Perkins	
Engine norm		Stage IIIA	
Max. fuel sulphur content		5000 ppm	
Engine model		1104D-44TA	
Number of cylinders / Capacity of cylinders		4 - 4400 cm³	
Engine power (Hp/kW)		101 Hp / 74.50 kW	
Max. torque / Engine rotation		400 Nm @ 1400 rpm	
Drawbar pull (Laden)		10000 daN	
Transmission			
Transmission type		Torque converter	
Number of gears (forward / reverse)		4 / 4	
Max. travel speed		24.90 km/h	
Parking brake		Automatic Negative Hand-brake	
Service brake		Oil-immersed multi-discs braking on front & rear axles	
Hydraulics			
Hydraulic pump type		Gear pump	
Hydraulic flow / Pressure		167 l/min-265 bar	
Tank capacities			
Engine oil		11.40 l	
Hydraulic oil		135 l	
Hydraulic tank capacity		175 l	
Fuel		140 l	
Noise and vibration			
Noise at driving position (LpA)		82 dB	
Noise to environment (LWA)		105 dB	
Vibration on hands/arms		2.50 m/s²	
Compatible platform			
Platform capacity	Q	1000 kg	
Number of people		3	
Platform dimensions (length x width)	Ip / ep	5000 m x 1200 m	
Platform weight*		1150 kg	
Miscellaneous			
Steering wheels (front / rear)		2 / 2	
Drive wheels (front / rear)		2 / 2	
Cab certification		Cabin ROPS - FOPS level 2	
Controls		JSM	

MT-X 1840 A - Dimensional drawing




MT-X 1840 A - Load chart


Machine on tires with forks - with levelling device Metric




Machine on lowered stabilisers with forks Metric



Machine on stabilisers with Man basket Metric



**Head Office**

B.P. 249 - 430 rue de l'Aubinière
44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes