Technical sheet:

# MT-X 1840







	мт-х 1840 Created on December 4, 2025 at 11:07 AM
Capacities	Metric
Max. capacity	4000 kg
Max. lifting height	17.55 m
Maximum outreach	13.08 m
Breakout force with bucket	7500 daN
Weight and dimensions	
Overall length to carriage	l11 6.16 m
Length to face of forks	12 6.27 m
Overall width	b1 2.42 m
Overall height	h17 2.45 m
Wheelbase	y 3.07 m
Ground clearance	m4 0.37 m
Overall cab width	b4 0.89 m
Tilt-up angle	a4 12 °
Tilt-down angle	a5 114°
External turning radius (over tyres)	Wa1 3.94 m
Unladen weight (with forks)	11630 kg
Overall weight	11600 kg
Tires type	Pneumatic
Standard tires	Alliance 400/80 - 24 -162A8
Forks length / width / section	I / e / s 1200 mm x 125 mm x 50 mm
Performances	
Lifting	17.30 s
Lowering	12.70 s
Extension	16.10 s
Retraction	15.60 s
Crowd	5 s
Dump	4 s
Engine	
Engine brand	Perkins
Engine norm	Stage IIIA
Engine model	1104D-44TA
Number of cylinders / Capacity of cylinders	4 - 4400 cm³
Engine power (Hp/kW)	101 Hp / 74.50 kW
Max. torque / Engine rotation	400 Nm @ 1400 rpm
Drawbar pull (Laden)	10000 daN
Transmission	
Transmission type	Torque converter
Number of gears (forward / reverse)	4 / 4
Max. travel speed	24.90 km/h
Max. travel speed (may vary according to applicable regulations)	24.90 km/h
Parking brake	Automatic Negative Hand-brake
raikilly blake	
Service brake	Oil-immersed multi-discs braking on front & re axles
Hydraulics	
Hydraulic pump type	Gear pump
Hydraulic flow / Pressure	167 l/min-270 bar
Tank capacities	
Engine oil	11.40
Hydraulic oil	1351
Hydraulic tank capacity	175
Fuel	140 l
Noise and vibration	140 1
Noise at driving position (LpA)	82 dB
Noise to environment (LwA)	105 dB
Vibration on hands/arms	< 2.50 m/s²
Miscellaneous	
Steering wheels (front / rear)	2/2
Drive wheels (front / rear)	2/2
Cab certification	Cabin ROPS - FOPS level 2
Controls	JSM

## MT-X 1840 - Dimensional drawing









### MT-X 1840 - Load chart

Machine on tires with forks - with levelling device Metric



#### Machine on lowered stabilisers with forks Metric







#### **Head Office**

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes