Technical sheet :

MTA 6034 53






мта боз4 sз Created on August 1, 2025 at 5:34 PM UTC
--

	MIA 6034 53	
Capacities		Metric
/ax. capacity		2721 kg
/ax. lifting height		10.44 m
faximum outreach		7.09 m
leight and dimensions		
verall length to carriage	11	4.88 m
verall width	b1	2.39 m
verall height	h17	2.36 m
heelbase	у	2.80 m
ound clearance	m4	356 mm
verall cab width	b4	762 mm
It-up angle	a4	12 °
It-down angle	a5	106 °
ternal turning radius	Wa3	3.81 m
nladen weight (with forks)		6855 kg
andard tires		15 x 19.5
ame leveling longitudinal +/-		10 °
rame leveling corrector	a9	10 °
erformances		
fting		11 s
owering		8 s
xtension		10 s
etraction		11 s
rowd		4 s
ump		3 s
ingine		
ngine brand		Deutz
ngine norm		Stage IV, Tier 4 final
ngine model		TD3.6 L4
umber of cylinders / Capacity of cylinders		4 - 3.62 cm ³
C. Engine power rating - Power		74.29 Hp / 55.40 kW
fax. torque / Engine rotation		330 Nm @ 330 rpm
ransmission		
ransmission type		Torque converter with powershift gearbox
umber of gears (forward / reverse)		3 / 3
ravel speed (laden)		29 km/h
arking brake		Hydraulic spring release SAHR
ervice brake		Wet disc brakes
xle Manufacturer		Dana
ydraulics		bund
ydraulic pump type		Gear pump
ydraulic flow / Pressure		110 l/min-207 bar
ank capacities		
ngine oil		8.90
ydraulic oil		133
uel tank		110
liscellaneous		1101
teering wheels (front / rear)		2/2
rive wheels (front / rear)		2/2
ab certification		Z / Z ROPS/FOPS
		RUPS/FUPS

MTA 6034 S3 - Dimensional drawing





Head Office B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes