


Technical sheet :

MTA 6034 S3



Capacities		Metric
Max. capacity		2721 kg
Max. lifting height		10.44 m
Max. outreach		7.09 m
Weight and dimensions		
Overall length to carriage	l11	4.88 m
Overall width	b1	2.39 m
Overall height	h17	2.36 m
Wheelbase	y	2.80 m
Ground clearance	m4	356 mm
Overall cab width	b4	762 mm
Tilt-up angle	a4	12 °
Tilt-down angle	a5	106 °
External turning radius	Wa3	3.81 m
Unladen weight (with forks)		6855 kg
Standard tires		15 x 19.5
Frame leveling longitudinal +/-		10 °
Frame leveling corrector	a9	10 °
Performances		
Lifting		11 s
Lowering		8 s
Extension		10 s
Retraction		11 s
Crowd		4 s
Dump		3 s
Engine		
Engine brand		Deutz
Engine norm		Stage IV / Tier 4 Final
Engine model		TD3.6 L4
Number of cylinders / Capacity of cylinders		4 - 3.62 cm³
I.C. Engine power rating - Power		74.29 Hp / 55.40 kW
Max. torque / Engine rotation		330 Nm @ 330 rpm
Transmission		
Transmission type		Torque converter with powershift gearbox
Number of gears (forward / reverse)		3 / 3
Travel speed (laden)		29 km/h
Parking brake		Hydraulic spring release SAHR
Service brake		Wet disc brakes
Axle Manufacturer		Dana
Hydraulics		
Hydraulic pump type		Gear pump
Hydraulic flow / Pressure		110 l/min-207 bar
Tank capacities		
Engine oil		8.90 l
Hydraulic oil		133 l
Fuel tank		110 l
Miscellaneous		
Steering wheels (front / rear)		2 / 2
Drive wheels (front / rear)		2 / 2
Safety cab homologation		ROPS/FOPS
Controls		Single Joystick FNR

MTA 6034 S3 - Dimensional drawing





Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes