

Technische fiche :

EMA II 13



 **MANITOU**
HANDLING YOUR WORLD

Technical characteristics			Metrisch	
1.1	Manufacturer			Manitou
1.2	Model Name			EMA II 13
1.3	Power source			Electrical
1.4	Operator type			Seated
1.5	Max. capacity	Q		1300 kg
1.6	Load center of gravity	c		500 mm
1.8	Load distance, centre of drive axle to fork	x		278 mm
1.9	Wheelbase	y		1855 mm
Weight				
2.1	Service weight			5900 kg
2.2	Weight on front axle (laden) / rear axle (laden)			3350 kg / 3850 kg
2.3	Weight on front axle (Unladen) / rear axle (Unladen)			1900 kg / 4000 kg
Wheels				
3.1	Tires type			Solid tires
3.2	Dimensions of front wheels			412 x 127 mm
3.3	Dimensions of rear wheels			457 x 152 mm
3.5	Number of front wheels / rear wheels			2 / 2
3.5.2	Number of drive wheels			2
3.6	Front wheel gauge	b10		825 mm
3.7	Rear wheel gauge	b11		1060 mm
Dimensions				
4.7	Height of overhead guard (cabin)	h6		2260 mm
4.8	Seat height/stand height	h7		1200 mm
4.19	Overall length	l1		3890 mm
4.20	Length to face of forks	l2		2740 mm
4.21	Overall width	b1		1060 mm
4.22	Forks section / width / length	s / e / l		40 mm x 100 mm x 1150 mm
4.23	Fork carriage ISO 2328 (class/form) A/B			2
4.24	Fork carriage width	b3		860 mm
4.31	Ground clearance below mast	m1		50 mm
4.32	Ground clearance at centre of wheelbase	m2		130 mm
4.33	Aisle Width for pallets 1000 x 1200 crossways	Ast		1700 mm
4.34	Aisle width for 800 x 1200 pallet lengthways	Ast		1900 mm
Performances				
5.1	Travel speed (laden / unladen)			9 km/h-9.50 km/h
5.2	Lifting speed (laden / unladen)			0.35 m/s-0.45 m/s
5.3	Lowering speed (laden / unladen)			0.40 m/s-0.35 m/s
5.7	Gradeability (laden / unladen)			8 % / 10.50 %
5.10	Service brake			Hydraulic
Engine				
6.1	Drive motor rating S2 60 min			10 kW
6.2	Lift motor rating at S3 15%			9 kW
6.3	Battery according to DIN 43531/35/36 A, B, C			DIN 43595
6.4	Battery voltage / capacity			48 V / 620 Ah
6.5	Battery weight (+/- 5%)			1030 kg
Miscellaneous				
8.1	Type of drive control			Mosfet AC speed controller
8.2	Working hydraulic pressure for attachments			200 bar
8.3	Oil flow rate for attachments			25 l/min
8.4	Measured/guaranteed mean noise level at the ear of the operator			< 73 dB
8.4	Sound level at the driver's ear according to DIN 12 053			73 dB

EMA II 13 - Tekening met afmetingen



Kenmerken van de masten en restcapaciteiten

Free Lift Triplex (FLT)		FLT 42	FLT 50	FLT 56	FLT 60	FLT 66	FLT 76
α - Mast/fork carriage tilt, forward	°	1	1	1	1	1	1
β - Mast/fork carriage tilt, backward	°	3	3	3	3	3	3
h1 - Mast lowered height	mm	2360	2630	2810	2960	3210	3650
h2 - Mast free lift	mm	1400	1750	193	2080	2330	2670
h3 - Mast lifting height	mm	4200	5010	5550	6000	6600	7620
h4 - Mast extended height	mm	5030	5910	6450	6900	7500	8520
Residual capacity with integrated side shift at max height	kg	1300	1200	1100	1000	900	750



 **MANITOU**
HANDLING YOUR WORLD

Hoofdkantoor

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - Frankrijk

Tel.: 00 33 (0)2 40 09 10 11 - Fax: 00 33 (0)2 40 09 10 97

www.manitou.com



Deze brochure beschrijft versies en configuratie-opties voor Manitou-producten die met verschillende apparatuur kunnen worden uitgerust. De uitrusting die in deze brochure wordt beschreven, kan standaard, optioneel of niet leverbaar zijn, afhankelijk van de uitvoering. Manitou behoudt zich het recht voor om de weergegeven en beschreven specificaties op elk moment en zonder kennisgeving vooraf te wijzigen. De fabrikant is niet aansprakelijk voor de gegeven specificaties. Neem voor meer informatie contact op met uw Manitou-dealer. Niet-contractueel document. De productbeschrijvingen kunnen afwijken van de werkelijke producten. De lijst met specificaties is niet allesomvattend. De logo's en visuele identiteit van het bedrijf zijn eigendom van Manitou en mogen niet zonder toestemming worden gebruikt. Alle rechten voorbehouden. De foto's en diagrammen in deze brochure zijn uitsluitend bedoeld voor raadpleging en informatie.

MANITOU BF SA - Naamloze vennootschap met raad van bestuur - Aandeelkapitaal: 39.668.399 euro - 857 802 508 RCS Nantes