

Technical sheet :

# EMA II 17

---



 **MANITOU**  
HANDLING YOUR WORLD

|       | Technical characteristics                                       |           | Metric                     |
|-------|---|-----------|----------------------------|
| 1.1   | Manufacturer  |           | Manitou                    |
| 1.2   | Model Name  |           | EMA II 17                  |
| 1.3   | Power source  |           | Electrical                 |
| 1.4   | Operator type   |           | Seated                     |
| 1.5   | Max. capacity   | Q         | 1700 kg                    |
| 1.6   | Load center of gravity  | c         | 500 mm                     |
| 1.8   | Load distance, centre of drive axle to fork                     | x         | 278 mm                     |
| 1.9   | Wheelbase   | y         | 1745 mm                    |
|       | Weight  |           |                            |
| 2.1   | Service weight  |           | 6000 kg                    |
| 2.2   | Weight on front axle (laden) / rear axle (laden)                |           | 4250 kg / 3250 kg          |
| 2.3   | Weight on front axle (Unladen) / rear axle (Unladen)            |           | 2000 kg / 4000 kg          |
|       | Wheels  |           |                            |
| 3.1   | Tires type  |           | Solid tires                |
| 3.2   | Dimensions of front wheels                                      |           | 412 x 152                  |
| 3.3   | Dimensions of rear wheels                                       |           | 457 x 152                  |
| 3.5   | Number of front wheels / rear wheels                            |           | 2 / 2                      |
| 3.5.2 | Number of drive wheels  |           | 2                          |
| 3.6   | Front wheel gauge   | b10       | 960 mm                     |
| 3.7   | Rear wheel gauge  | b11       | 1080 mm                    |
|       | Dimensions  |           |                            |
| 4.7   | Height of overhead guard (cabin)                                | h6        | 2260 mm                    |
| 4.8   | Seat height/stand height  | h7        | 1200 mm                    |
| 4.19  | Overall length  | l1        | 3710 mm                    |
| 4.20  | Length to face of forks   | l2        | 2560 mm                    |
| 4.21  | Overall width   | b1        | 1080 mm                    |
| 4.22  | Forks section / width / length                                  | s / e / l | 40 mm x 100 mm x 1150 mm   |
| 4.23  | Fork carriage ISO 2328 (class/form) A/B                         |           | 2                          |
| 4.24  | Fork carriage width   | b3        | 860 mm                     |
| 4.31  | Ground clearance below mast                                     | m1        | 50 mm                      |
| 4.32  | Ground clearance at centre of wheelbase                         | m2        | 130 mm                     |
| 4.33  | Aisle Width for pallets 1000 x 1200 crossways                   | Ast       | 1800 mm                    |
| 4.34  | Aisle width for 800 x 1200 pallet lengthways                    | Ast       | 2000 mm                    |
|       | Performances  |           |                            |
| 5.1   | Travel speed (laden / unladen)                                  |           | 9 km/h-9.50 km/h           |
| 5.2   | Lifting speed (laden / unladen)                                 |           | 0.35 m/s-0.45 m/s          |
| 5.3   | Lowering speed (laden / unladen)                                |           | 0.40 m/s-0.36 m/s          |
| 5.7   | Gradeability (laden / unladen)                                  |           | 8 % / 10.50 %              |
| 5.10  | Service brake   |           | Hydraulic                  |
|       | Engine  |           |                            |
| 6.1   | Drive motor rating S2 60 min                                    |           | 10 kW                      |
| 6.2   | Lift motor rating at S3 15%                                     |           | 9 kW                       |
| 6.3   | Battery according to DIN 43531/35/36 A, B, C                    |           | DIN 43595                  |
| 6.4   | Battery voltage / capacity                                      |           | 48 V / 620 Ah              |
| 6.5   | Battery weight (+/- 5%)   |           | 1030 kg                    |
|       | Miscellaneous   |           |                            |
| 8.1   | Type of drive control   |           | Mosfet AC speed controller |
| 8.2   | Working hydraulic pressure for attachments                      |           | 200 bar                    |
| 8.3   | Oil flow rate for attachments                                   |           | 25 l/min                   |
| 8.4   | Measured/guaranteed mean noise level at the ear of the operator |           | < 73 dB                    |
| 8.4   | Sound level at the driver's ear according to DIN 12 053         |           | 73 dB                      |

## EMA II 17 - Dimensional drawing



# Characteristics of masts and residual capacities

| Free Lift Triplex (FLT)                                   |    | FLT 39 | FLT 42 | FLT 46 | FLT 48 | FLT 50 | FLT 52 | FLT 56 | FLT 60 | FLT 66 | FLT 72 | FLT 76 |
|---|----|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| α - Mast/fork camiage tilt, forward                       | °  | 1      | 1      | 1      | 1      | 1      | 1      | 1      | 1      | 1      | 1      | 1      |
| β - Mast/fork camiage tilt, backward                      | °  | 3      | 3      | 3      | 3      | 3      | 3      | 3      | 3      | 3      | 3      | 3      |
| h1 - Mast lowered height                                  | mm | 2210   | 2300   | 2440   | 2500   | 2570   | 2640   | 2750   | 2900   | 3150   | 3400   | 3590   |
| h2 - Mast free lift                                       | mm | 1390   | 1480   | 1620   | 1680   | 1750   | 1820   | 1930   | 2080   | 23300  | 2580   | 2770   |
| h3 - Mast lifting height                                  | mm | 3930   | 4200   | 4620   | 4800   | 5010   | 5220   | 5550   | 6000   | 6600   | 7200   | 7620   |
| h4 - Mast extended height                                 | mm | 4760   | 5030   | 5450   | 5630   | 5840   | 6050   | 6380   | 6830   | 7430   | 8030   | 8450   |
| Residual capacity with integrated side shift at max heigh | kg | 1250   | 1300   | 1300   | 1200   | 1200   | 1200   | 1200   | 1100   | 950    | 900    | 900    |



**Head Office**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes