Technical sheet:

100 SC






Capacities		
		Metric
Working height	h21	9.70 m
Platform height	h7	7.70 m
Platform capacity	Q	680 kg
Max. capacity on the extension deck		136 kg
Number of people (indoor / outdoor)		4 / 4
Weight and dimensions		
Platform weight*		3653 kg
Platform dimensions (length x width)	lp / ep	2.79 m x 1.60 m
Platform dimensions with extension (length x width)		4.31 m x 1.60 m
Overall length	l1	3.76 m
Overall width	b1	1.75 m
Overall height	h17	2.59 m
Overall height (stowed)	h18 ***	1.92 m
Overall length with platform extension	l15	4.81 m
External turning radius	Wa3	4.60 m
Ground clearance at centre of wheelbase	m2	0.24 m
Wheelbase	у	2.29 m
Performances		
Drive speed - stowed		5.60 km/h
Drive speed - raised		0.40 km/h
Raise speed (laden) / Lower speed (laden)		36 s / 33 s
Gradeability		35 %
Max outrigger leveling front uphill / back uphill		5.30 ° / 4.20 °
Max outrigger leveling side to side		11.70 °
Indoor and outdoor max Tilt Rating (Fore and Aft / Side-to-Side)		3°/2°
Wheels		
Tires type		Foam-filled
Drive wheels (front / rear)		2/2
Steering wheels (front / rear)		2 / 0
Braking wheels (front / rear)		2/2
Engine/Battery		
Drive motor power rating		18.50 kW
Engine brand / model		Kubota - D1105
Engine norm		Tier 4 final
Engine power (Hp / kW)		25 Hp / 18.50 kW
Miscellaneous		
Ground Pressure		5.14 dan/cm2
Hydraulic tank capacity		68.10 l
Fuel		37.90 l
Sound pressure level (ground workstation)		85 dB
Sound pressure level (platform work station) (LpA)		79 dB
Vibration on hands/arms		2.50 m/s ²
Standards compliance		
This machine is in compliance with:		European directives: 2006/42/EC- Machinery (revised EN280:2013) - 2004/108/EC (EMC)


^{*}Varies according to options and standards of the country to which the machine is delivered *** With folded guardrail


100 SC - Load chart


Load Chart for MEWP Metric



100 SC - Dimensional drawing








Equipment

230V Predisposition 4 wheel drive Anti-slip platform surface Audible alarm and illuminated indicator lamp (leveling, overload, lowering) CAN bus technology Emergency stop button in platform and on frame Engine mounted on sliding platform Fixed anti-shearing protection Fold away guard rails with full height swing gate Horn in the platform Hour meter Integrated diagnostic assistance Lowering alarm Oscillating front axle Platform access gate Proportional controls Removable control unit Stabilizers with automatic leveling Travel possible at maximum height

Optional 2 flashing lights on frame Biodegradable oil Lights Non-marking thes Safety harness

Working headlight in platform





Head Office

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes