

Technical sheet :


ES 820



 **MANITOU**
HANDLING YOUR WORLD

Technical characteristics		Metric	
1.1	Manufacturer		Manitou
1.2	Model Name		ES 820
1.3	Power source		Electrical - Lead
1.4	Operator type		Pedestrian
1.5	Max. capacity	Q	2000 kg
1.6	Load center of gravity	c	600 mm
1.8	Distance from Load backrest to center of rear axle	x	661 mm
1.9	Wheelbase	y	1378 mm
Weight			
2.1	Service weight		1620 kg
2.2	Weight on front axle (laden) / rear axle (laden)		1180 kg / 2510 kg
2.3	Weight on front axle (Unladen) / rear axle (Unladen)		1125 kg / 495 kg
Wheels			
3.1	Tires type		Polyurethane cushion
3.3	Number of load wheels / Size of load wheels		2 / 82x68
3.4	Number of stabilizer wheels / Size of the stabilizer wheels		2 / 120x50
3.5	Number of front wheels / rear wheels		3 / 4
3.5.2	Number of drive wheels / Size of drive wheels		1/254x100
3.6	Front wheel gauge	b10	664 mm
3.7	Rear wheel gauge	b11	393 mm
Dimensions			
4.15	Fork height in low position	h13	82 mm
4.19	Overall length	l1	2048 mm
4.20	Length to face of forks	l2	898 mm
4.21	Overall width	b1	890 mm
4.22	Forks section / width / length	s / e / l	70 mm / 185 mm / 1150 mm
4.24	Fork carriage width	b3	700 m
4.31	Ground clearance below mast	m1	30 mm
4.32	Ground clearance at centre of wheelbase	m2	25 mm
4.33	Aisle Width for pallets 1000 x 1200 crossways	Ast	2469 mm
4.34	Aisle width for 800 x 1200 pallet lengthways	Ast	2448 mm
4.35	Turning radius	Wa	1591 mm
4.9	Height tiller min. / max.	h14 / h14	975 mm / 1375 mm
Performances			
5.1	Travel speed (laden / unladen)		6 km/h / 6 km/h
5.2	Lifting speed (laden / unladen)		0.11 m/s / 0.20 m/s
5.3	Lowering speed (laden / unladen)		0.21 m/s / 0.22 m/s
5.8	Max Gradeability (laden / unladen)		6 % / 10 %
5.10	Service brake		Electro magnetic
Engine			
6.1	Drive motor rating S2 60 min		2 kW
6.2	Lift motor rating at S3 15%		4 kW
6.3	Battery according to DIN 43531/35/36 A, B, C		Traction
6.4	Battery voltage / capacity		24 V / 315 Ah
6.5	Battery weight (+/- 5%)		273 kg
Miscellaneous			
8.1	Type of drive control		AC
8.4	Sound level at the driver's ear according to DIN 12 053		65 dB

ES 820 - Dimensional drawing



Characteristics of masts and residual capacities

Central Cylinder Duplex (CCD)	FVD 29	FVD 34
h1 - Mast lowered height	mm	1940
h3 - Mast lifting height	mm	2940
h4 - Mast extended height	mm	3365
Residual capacity at max height	kg	1600
		2190
		3440
		3865
		1300

Central Cylinder Simplex (CCS)	CCS 15	CCS 17
h1 - Mast lowered height	mm	1940
h2 - Mast free lift	mm	1510
h3 - Mast lifting height	mm	1510
h4 - Mast extended height	mm	1940
Residual capacity at max height	kg	2000
		2190
		1760
		1760
		2190
		2000

Free Lift Duplex (FLD)	FLD 29	FLD 34
h1 - Mast lowered height	mm	1940
h2 - Mast free lift	mm	1510
h3 - Mast lifting height	mm	2935
h4 - Mast extended height	mm	3365
Residual capacity at max height	kg	1600
		2190
		1760
		3435
		3865
		1300

Free Lift Triplex (FLT)	FLT 42	FLT 47	FLT 54
h1 - Mast lowered height	mm	1900	2060
h2 - Mast free lift	mm	1465	1625
h3 - Mast lifting height	mm	4245	4725
h4 - Mast extended height	mm	4710	5190
Residual capacity at max height	kg	750	550
		2300	1875
		5455	5880
		450	


Head Office

B.P. 249 - 430 rue de l'Aubinière
 44150 Ancenis Cedex - France
 Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97
www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes