

Ficha técnica :

KLEOS EB 500 D25



 **MANITOU**
HANDLING YOUR WORLD

| Technical characteristics | | | Métrico | | |
|---------------------------|---|----|---------|--|---------------------|
| 1.1 | Manufacturer | | | | Manitou |
| 1.2 | Model Name | | | | EB 500 D25 |
| 1.3 | Power source | | | | Electrical |
| 1.4 | Operator type | | | | Pedestrian |
| 1.5 | Max. capacity | Q | | | 500 kg |
| 1.6 | Load center of gravity | c | | | 250 mm |
| Weight | | | | | |
| 2.1 | Overall weight without tools | | | | 240 kg |
| Wheels | | | | | |
| 3.1 | Tires type | | | | Nylon |
| 3.2 | Dimensions of front wheels | | | | 2x (75x65) |
| 3.3 | Dimensions of rear wheels | | | | 2x (150x50) |
| Dimensions | | | | | |
| 4.2 | Mast lowered height | h1 | | | 1950 mm |
| 4.5 | Mast extended height | h4 | | | 3190 mm |
| 4.19 | Overall length | l1 | | | 1300 mm |
| 4.20 | Length to face of forks | l2 | | | 575 mm |
| 4.21 | Overall width | b1 | | | 710 mm |
| 4.25 | Fork spread | b5 | | | 519 mm |
| 4.32 | Ground clearance at centre of wheelbase | m2 | | | 35 mm |
| Performances | | | | | |
| 5.2 | Lifting speed (laden / unladen) | | | | 0.07 m/s / 0.07 m/s |
| 5.3 | Lowering speed (laden / unladen) | | | | 0.10 m/s / 0.10 m/s |
| 5.11 | Parking brake | | | | Mecanic |
| Engine | | | | | |
| 6.4 | Battery voltage / capacity | | | | 12 V / 110 Ah |
| 7.2 | Power | | | | 1.20 kW |
| Miscellaneous | | | | | |
| 8.4 | Sound level at the driver's ear according to DIN 12 053 | | | | 65 dB |

Kleos EB 500 D25 - Diagrama dimensional



Características de las herramientas

| Herramienta 500 kg | Capacidad del accesorio kg | Centro de gravedad de la carga mm | A1 mm | A2 mm | B mm | B1 mm | C mm | D mm | E mm | E1 mm | E2 mm | F mm | Peso kg |
|--------------------|----------------------------|-----------------------------------|-------|-------|------|-------|------|------|------|-------|-------|------|---------|
| EPE 500 | 500 | 350 | 700 | 715 | 50 | - | 252 | - | - | - | - | 320 | 30 |
| FA 500 | 500 | 350 | 700 | 745 | - | 250 | 680 | 45 | 60 | 30 | - | 720 | 54 |
| FR 500 | 500 | 600 | 1150 | 1177 | 560 | 200 | 315 | 85 | - | 70 | - | 700 | 68 |
| FUT 500 | 300 | 600 | 795 | 650 | 1057 | 350 | 650 | 245 | - | 240 | 631 | - | 92 |
| PLF 500 | 500 | 350 | 700 | 727 | 600 | - | 280 | - | 91 | - | - | 630 | 50 |
| POT 500 | 250 | 600 | 625 | 652 | 50 | - | 150 | - | - | - | - | 320 | 25 |

Tools


EPE 500




FA 500



FR 500



FUT 500



PLF 500



POT 500





Oficina Central

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - Francia

Tel.: 00 33 (0)2 40 09 10 11 - Fax: 00 33 (0)2 40 09 10 97

www.manitou.com



Esta publicación describe las versiones y posibilidades de configuración de los productos Manitou que puedan diferir en equipamiento. Los equipamientos presentados en este folleto pueden ser de serie, opcionales o no estar disponibles en algunas versiones. Manitou se reserva el derecho, en cualquier momento y sin previo aviso, de modificar las especificaciones descritas y representadas. Las especificaciones aportadas no comprometen al fabricante. Para más información, póngase en contacto con su concesionario Manitou. Documento no contractual. Presentación de los productos no contractual. Lista de especificaciones no exhaustiva. Los logos y la identidad visual de la empresa son propiedad de Manitou y no pueden ser utilizados sin autorización. Todos los derechos reservados. Las fotos y los esquemas contenidos en este folleto se ofrecen para consulta y a título indicativo solamente.

Manitou BF SA - Sociedad anónima con Consejo de Administración - Capital social: 39 668 399 euros - 857 802 508 RCS Nantes