

Technisches Datenblatt :

# ME 430



 **MANITOU**  
HANDLING YOUR WORLD

|       | Technical characteristics                                       |           | Metrisch                 |
|-------|-----------------------------------------------------------------|-----------|--------------------------|
| 1.1   | Manufacturer                                                    |           | Manitou                  |
| 1.2   | Model Name                                                      |           | ME 430                   |
| 1.3   | Power source                                                    |           | Electrical               |
| 1.4   | Operator type                                                   |           | Seated                   |
| 1.5   | Max. capacity                                                   | Q         | 3000 kg                  |
| 1.6   | Load center of gravity                                          | c         | 500 mm                   |
| 1.8   | Load distance, centre of drive axle to fork                     | x         | 445 mm                   |
| 1.9   | Wheelbase                                                       | y         | 1750 mm                  |
|       | <b>Weight</b>                                                   |           |                          |
| 2.1   | Service weight                                                  |           | 5250 kg                  |
| 2.2   | Weight on front axle (laden) / rear axle (laden)                |           | 7340 kg / 980 kg         |
| 2.3   | Weight on front axle (Unladen) / rear axle (Unladen)            |           | 2572 kg / 2578 kg        |
|       | <b>Wheels</b>                                                   |           |                          |
| 3.1   | Tires type                                                      |           | Solid tires              |
| 3.2   | Dimensions of front wheels                                      |           | 23 x 9-10                |
| 3.3   | Dimensions of rear wheels                                       |           | 18 x 7-8                 |
| 3.5   | Number of front wheels / rear wheels                            |           | 2 / 2                    |
| 3.5.2 | Number of drive wheels                                          |           | 2                        |
| 3.6   | Front wheel gauge                                               | b10       | 1073 mm                  |
| 3.7   | Rear wheel gauge                                                | b11       | 960 mm                   |
|       | <b>Dimensions</b>                                               |           |                          |
| 4.7   | Height of overhead guard (cabin)                                | h6        | 2240 mm                  |
| 4.8   | Seat height/stand height                                        | h7        | 1190 mm                  |
| 4.12  | Height of towing bar (coupling height)                          | h10       | 625 mm                   |
| 4.19  | Overall length                                                  | l1        | 3645 mm                  |
| 4.20  | Length to face of forks                                         | l2        | 2495 mm                  |
| 4.21  | Overall width                                                   | b1        | 1275 mm                  |
| 4.22  | Forks section / width / length                                  | s / e / l | 45 mm x 122 mm x 1150 mm |
| 4.23  | Fork carriage ISO 2328 (class/form) A/B                         |           | 3A                       |
| 4.24  | Fork carriage width                                             | b3        | 1100 mm                  |
| 4.31  | Ground clearance below mast                                     | m1        | 105 mm                   |
| 4.32  | Ground clearance at centre of wheelbase                         | m2        | 115 mm                   |
| 4.33  | Aisle Width for pallets 1000 x 1200 crossways                   | Ast       | 4045 mm                  |
| 4.34  | Aisle width for 800 x 1200 pallet lengthways                    | Ast       | 4245 mm                  |
| 4.35  | Turning radius                                                  | Wa        | 2400 mm                  |
| 4.36  | Internal turning radius (over tyres)                            | b13       | 730 mm                   |
|       | <b>Performances</b>                                             |           |                          |
| 5.1   | Travel speed (laden / unladen)                                  |           | 19 km/h-20 km/h          |
| 5.2   | Lifting speed (laden / unladen)                                 |           | 0.42 m/s-0.54 m/s        |
| 5.3   | Lowering speed (laden / unladen)                                |           | 0.47 m/s-0.42 m/s        |
| 5.5   | Drawbar pull (Laden / Unladen)                                  |           | 1740 daN / 1680 daN      |
| 5.7   | Gradeability (laden / unladen)                                  |           | 14 % / 20 %              |
| 5.10  | Service brake                                                   |           | Oil bath                 |
|       | <b>Engine</b>                                                   |           |                          |
| 6.1   | Drive motor rating S2 60 min                                    |           | 18.50 kW                 |
| 6.2   | Lift motor rating at S3 15%                                     |           | 25.40 kW                 |
| 6.3   | Battery according to DIN 43531/35/36 A, B, C                    |           | DIN43536 A               |
| 6.4   | Battery voltage / capacity                                      |           | 80 V / 700 Ah            |
| 6.6   | Energy consumption                                              |           | 11.50 kWh                |
|       | <b>Miscellaneous</b>                                            |           |                          |
| 8.1   | Type of drive control                                           |           | Electronic               |
| 8.2   | Working hydraulic pressure for attachments                      |           | 210 bar                  |
| 8.3   | Oil flow rate for attachments                                   |           | 65 l/min                 |
| 8.4   | Measured/guaranteed mean noise level at the ear of the operator |           | < 72 dB                  |
| 8.4   | Sound level at the driver's ear according to DIN 12 053         |           | 72 dB                    |

## ME 430 - Maßzeichnung



## Technische Daten und Resttragfähigkeiten der Hubgerüste

| Full Visibility Duplex (FVD)                               |    | FVD 30 | FVD 33 | FVD 35 | FVD 37 | FVD 40 | FVD 43 | FVD 45 | FVD 48 | FVD 50 |
|------------------------------------------------------------|----|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| Mast/fork carriage tilt, forward                           | °  | 5      | 5      | 5      | 5      | 5      | 5      | 5      | 5      | 5      |
| Mast/fork carriage tilt, backward                          | °  | 8      | 8      | 8      | 8      | 8      | 5      | 5      | 5      | 5      |
| h1 - Mast lowered height                                   | mm | 2235   | 2385   | 2485   | 285    | 2835   | 2985   | 3085   | 3235   | 3335   |
| h2 - Mast free lift                                        | mm | 145    | 145    | 145    | 145    | 145    | 145    | 145    | 145    | 145    |
| h3 - Mast lifting height                                   | mm | 3000   | 3300   | 3500   | 3700   | 4000   | 4300   | 4500   | 4800   | 5000   |
| h4 - Mast extended height                                  | mm | 3838   | 4138   | 4338   | 4538   | 4838   | 5138   | 5338   | 5638   | 5838   |
| Residual capacity at max height                            | kg | 3000   | 3000   | 3000   | 3000   | 3000   | 3000   | 3000   | 3000   | 3000   |
| Residual capacity with integrated side shift at max height | kg | 3000   | 3000   | 3000   | 3000   | 3000   | 3000   | 3000   | 3000   | 3000   |
| Residual capacity with hooked-on side shift at max height  | kg | 3000   | 3000   | 3000   | 3000   | 3000   | 3000   | 2950   | 2900   | 2800   |
| Height at max capacity                                     | mm | 3000   | 3300   | 3500   | 3700   | 4000   | 4300   | 4500   | 4800   | 5000   |
| Height at max capacity with integrated sideshift           | mm | 3000   | 3300   | 3500   | 3700   | 4000   | 4300   | 4500   | 4800   | 5000   |

| Free Lift Duplex (FLD)                                     |    | FLD 30 | FLD 33 | FLD 37 | FLD 40 |
|------------------------------------------------------------|----|--------|--------|--------|--------|
| Mast/fork carriage tilt, forward                           | °  | 5      | 5      | 5      | 5      |
| Mast/fork carriage tilt, backward                          | °  | 8      | 8      | 8      | 8      |
| h1 - Mast lowered height                                   | mm | 2135   | 2285   | 2485   | 2685   |
| h2 - Mast free lift                                        | mm | 1275   | 1425   | 1625   | 1825   |
| h3 - Mast lifting height                                   | mm | 3000   | 3300   | 3700   | 4000   |
| h4 - Mast extended height                                  | mm | 3860   | 4160   | 4560   | 4860   |
| Residual capacity at max height                            | kg | 3000   | 3000   | 3000   | 3000   |
| Residual capacity with integrated side shift at max height | kg | 3000   | 3000   | 3000   | 3000   |
| Residual capacity with hooked-on side shift at max height  | kg | 3000   | 3000   | 3000   | 3000   |
| Height at max capacity                                     | mm | 3000   | 3300   | 3700   | 4000   |
| Height at max capacity with integrated sideshift           | mm | 3000   | 3300   | 3700   | 4000   |

| Free Lift Triplex (FLT)                                    |    | FLT 40 | FLT 43 | FLT 48 | FLT 50 | FLT 55 | FLT 60 |
|------------------------------------------------------------|----|--------|--------|--------|--------|--------|--------|
| Mast/fork carriage tilt, forward                           | °  | 5      | 5      | 5      | 5      | 5      | 5      |
| Mast/fork carriage tilt, backward                          | °  | 5      | 5      | 5      | 5      | 5      | 5      |
| h1 - Mast lowered height                                   | mm | 2035   | 2135   | 2285   | 2385   | 2585   | 2835   |
| h2 - Mast free lift                                        | mm | 1250   | 1350   | 1500   | 1600   | 1800   | 2050   |
| h3 - Mast lifting height                                   | mm | 4000   | 4300   | 4800   | 5000   | 5500   | 6000   |
| h4 - Mast extended height                                  | mm | 4785   | 5085   | 5585   | 5785   | 6285   | 6785   |
| Residual capacity at max height                            | kg | 3000   | 3000   | 3000   | 3000   | 2900   | 2700   |
| Residual capacity with integrated side shift at max height | kg | 3000   | 3000   | 3000   | 2900   | 2800   | 2650   |
| Residual capacity with hooked-on side shift at max height  | kg | 2900   | 2900   | 2850   | 2750   | 2550   | 2450   |
| Height at max capacity                                     | mm | 4000   | 4300   | 4800   | 5000   | 4000   | 4000   |
| Height at max capacity with integrated sideshift           | mm | 4000   | 4300   | 4800   | 4000   | 4000   | 4000   |

**Hauptsitz**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)

Diese Publikation enthält eine Beschreibung der Konfigurationsvarianten und Optionen für Manitou-Produkte, die je nach Ausstattung unterschiedlich sein können. Die in dieser Broschüre vorgestellten Ausstattungen können Teil einer Serie, als Option erhältlich oder je nach Ausführung nicht verfügbar sein. Manitou behält sich das Recht vor, die beschriebenen und dargestellten Spezifikationen jederzeit und ohne Vorankündigung zu ändern. Die angegebenen Spezifikationen sind für den Hersteller nicht bindend. Für weitere Einzelheiten wenden Sie sich bitte an Ihren Manitou-Händler. Es handelt sich nicht um ein vertraglich bindendes Dokument. Die Darstellung der Produkte ist vertraglich nicht bindend. Die Liste der Spezifikationen ist nicht vollständig. Die Logos sowie die visuelle Identität des Unternehmens sind Eigentum von Manitou und dürfen nicht ohne Genehmigung verwendet werden. Alle Rechte vorbehalten. Die in dieser Broschüre enthaltenen Fotos und Diagramme werden nur zu Anschauungs- und Informationszwecken zur Verfügung gestellt.

MANITOU BF SA - Gesellschaft mit beschränkter Haftung mit Verwaltungsrat - Aktienkapital: 39 668 399 Euro - 857 802 508 RCS Nantes