

Technical sheet :

# ME 320



 **MANITOU**  
HANDLING YOUR WORLD

| Technical characteristics |   | Metric    |                          |
|---------------------------|---|-----------|--------------------------|
| 1.1                       | Manufacturer  |           | Manitou                  |
| 1.2                       | Model Name  |           | ME 320                   |
| 1.3                       | Power source  |           | Electrical               |
| 1.4                       | Operator type   |           | Seated                   |
| 1.5                       | Max. capacity   | Q         | 2000 kg                  |
| 1.6                       | Load center of gravity  | c         | 500 mm                   |
| 1.8                       | Load distance, centre of drive axle to fork                     | x         | 355 mm                   |
| 1.9                       | Wheelbase   | y         | 1465 mm                  |
| Weight                    |   |           |                          |
| 2.1                       | Service weight  |           | 3470 kg                  |
| 2.2                       | Weight on front axle (laden) / rear axle (laden)                |           | 4750 kg / 720 kg         |
| 2.3                       | Weight on front axle (Unladen) / rear axle (Unladen)            |           | 1530 kg / 1940 kg        |
| Wheels                    |   |           |                          |
| 3.1                       | Tires type  |           | Solid tires              |
| 3.2                       | Dimensions of front wheels                                      |           | 200/50-10                |
| 3.3                       | Dimensions of rear wheels                                       |           | 15x4,5-8                 |
| 3.5                       | Number of front wheels / rear wheels                            |           | 2 / 1                    |
| 3.5.2                     | Number of drive wheels  |           | 2                        |
| 3.6                       | Front wheel gauge   | b10       | 910 mm                   |
| 3.7                       | Rear wheel gauge  | b11       | 175 mm                   |
| Dimensions                |   |           |                          |
| 4.7                       | Height of overhead guard (cabin)                                | h6        | 2040 mm                  |
| 4.8                       | Seat height/stand height  | h7        | 1000 mm                  |
| 4.12                      | Height of towing bar (coupling height)                          | h10       | 500 mm                   |
| 4.19                      | Overall length  | l1        | 3076 mm                  |
| 4.20                      | Length to face of forks   | l2        | 2006 mm                  |
| 4.21                      | Overall width   | b1        | 1120 mm                  |
| 4.22                      | Forks section / width / length                                  | s / e / l | 40 mm x 122 mm x 1070 mm |
| 4.23                      | Fork carriage ISO 2328 (class/form) A/B                         |           | 2A                       |
| 4.24                      | Fork carriage width   | b3        | 1000 mm                  |
| 4.31                      | Ground clearance below mast                                     | m1        | 100 mm                   |
| 4.32                      | Ground clearance at centre of wheelbase                         | m2        | 110 mm                   |
| 4.33                      | Aisle Width for pallets 1000 x 1200 crossways                   | Ast       | 3346 mm                  |
| 4.34                      | Aisle width for 800 x 1200 pallet lengthways                    | Ast       | 3470 mm                  |
| 4.35                      | Turning radius  | Wa        | 1660 mm                  |
| Performances              |   |           |                          |
| 5.1                       | Travel speed (laden / unladen)                                  |           | 15 km/h-15 km/h          |
| 5.2                       | Lifting speed (laden / unladen)                                 |           | 0.40 m/s-0.45 m/s        |
| 5.3                       | Lowering speed (laden / unladen)                                |           | 0.47 m/s-0.42 m/s        |
| 5.5                       | Drawbar pull (Laden / Unladen)                                  |           | 900 daN / 930 daN        |
| 5.7                       | Gradeability (laden / unladen)                                  |           | 13 % / 15 %              |
| 5.10                      | Service brake   |           | Oil bath                 |
| Engine                    |   |           |                          |
| 6.1                       | Number of drive motor / Drive motor rating S2 60 min            |           | 2 / 4.50 kW              |
| 6.2                       | Lift motor rating at S3 15%                                     |           | 8.60 kW                  |
| 6.3                       | Battery according to DIN 43531/35/36 A, B, C                    |           | DIN43531 A               |
| 6.4                       | Battery voltage / capacity                                      |           | 48 V / 690 Ah            |
| 6.6                       | Energy consumption according to VDI cycle (kWh/h)               |           | 4.70 kWh                 |
| Miscellaneous             |   |           |                          |
| 8.1                       | Type of drive control   |           | Electronic               |
| 8.2                       | Working hydraulic pressure for attachments                      |           | 180 bar                  |
| 8.3                       | Oil flow rate for attachments                                   |           | 35 l/min                 |
| 8.4                       | Measured/guaranteed mean noise level at the ear of the operator |           | < 70 dB                  |
| 8.4                       | Sound level at the driver's ear according to DIN 12 053         |           | 70 dB                    |

### ME 320 - Dimensional drawing







**Head Office**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes