

Technical sheet :

MI-X 80 D



 **MANITOU**
HANDLING YOUR WORLD

Technical characteristics			Metric	
1.1	Manufacturer			Manitou
1.2	Model Name			MI-X 80 D
1.3	Power source			Diesel
1.4	Operator type			Seated
1.5	Max. capacity	Q		8000 kg
1.6	Load center of gravity	c		600 mm
1.8	Load distance, centre of drive axle to fork	x		705 mm
1.9	Wheelbase	y		2500 mm
Weight				
2.1	Service weight			11790 kg
2.2	Weight on front axle (laden) / rear axle (laden)			17670 kg / 2120 kg
Wheels				
3.1	Tires type			Pneumatic
3.2	Dimensions of front wheels			9.00-20-14PR
3.3	Dimensions of rear wheels			9.00-20-14PR
3.5	Number of front wheels / rear wheels			4 / 2
3.5.2	Number of drive wheels			4
3.6	Front wheel gauge	b10		1628 mm
3.7	Rear wheel gauge	b11		1700 mm
Dimensions				
4.7	Height of overhead guard (cabin)	h6		2580 mm
4.8	Seat height/stand height	h7		1505 mm
4.12	Height of towing bar (coupling height)	h10		505 mm
4.19	Overall length	l1		5395 mm
4.20	Length to face of forks	l2		3895 mm
4.21	Overall width	b1		2165 mm
4.21	Overall width - Single wheels	b1		2165 mm
4.22	Forks section / width / length	s / e / l		75 mm x 160 mm x 1520 mm
4.23	Fork carriage ISO 2328 (class/form) A/B			4A
4.31	Ground clearance below mast	m1		185 mm
4.32	Ground clearance at centre of wheelbase	m2		339 mm
4.33	Aisle Width for pallets 1000 x 1200 crossways	Ast		5637 mm
4.34	Aisle width for 800 x 1200 pallet lengthways	Ast		5803 mm
4.36	Internal turning radius (over tyres)	b13		1327 mm
Performances				
5.1	Travel speed (laden / unladen)			28 km/h-32 km/h
5.2	Lifting speed (laden / unladen)			0.43 m/s-0.46 m/s
5.3	Lowering speed (laden / unladen)			0.45 m/s-0.36 m/s
5.5	Drawbar pull (Laden / Unladen)			7860 daN / 4500 daN
5.7	Gradeability (laden / unladen)			44 % / 44 %
5.10	Service brake			Hydraulic
Engine				
7.1	Engine brand / model			Cummins / QSB4,5
7.2	I.C. Engine power rating			82 kW
7.3	Rated speed			2200 rpm
7.4	Number of cylinders / Capacity of cylinders			4 - 4500 cm³
Miscellaneous				
8.3	Oil flow rate for attachments			180 l/min
8.4	Measured/guaranteed mean noise level at the ear of the operator			< 88 dB
8.4	Sound level at the driver's ear according to DIN 12 053			88 dB

MI-X 80 D - Dimensional drawing



Characteristics of masts and residual capacities

Full Visibility Duplex (FVD)		FVD 30	FVD 33	FVD 36	FVD 40	FVD 45	FVD 50
α - Mast/fork carriage tilt, forward	°	6	6	6	6	6	6
β - Mast/fork carriage tilt, backward	°	12	12	12	12	6	6
h1 - Mast lowered height	mm	2700	2850	3000	3200	3500	3750
h2 - Mast free lift	mm	200	200	200	200	200	200
h3 - Mast lifting height	mm	3000	3300	3600	4000	4500	5000
h4 - Mast extended height	mm	4210	4510	4810	5210	5710	6210
Residual capacity at max height	kg	8000	8000	8000	8000	8000	8000
Height at max capacity	mm	3000	3300	3600	4000	4500	5000

Free Lift Triplex (FLT)		FLT 45	FLT 48	FLT 50	FLT 55	FLT 60
α - Mast/fork carriage tilt, forward	°	6	6	6	3	3
β - Mast/fork carriage tilt, backward	°	6	6	6	6	6
h1 - Mast lowered height	mm	2750	2850	2950	3100	3250
h2 - Mast free lift	mm	1485	1585	1600	1800	1985
h3 - Mast lifting height	mm	4500	4800	5000	5500	6000
h4 - Mast extended height	mm	5775	6075	6360	6810	7275
Residual capacity at max height	kg	7000	7000	6500	6100	5600
Height at max capacity	mm	4500	4800	5000	5500	6000



Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes