

Technisches Datenblatt :


# ME 315 C



 **MANITOU**  
HANDLING YOUR WORLD

|       | Technical characteristics                                       |           | Metrisch                 |
|-------|-----------------------------------------------------------------|-----------|--------------------------|
| 1.1   | Manufacturer                                                    |           | Manitou                  |
| 1.2   | Model Name                                                      |           | ME 315c                  |
| 1.3   | Power source                                                    |           | Electrical               |
| 1.4   | Operator type                                                   |           | Seated                   |
| 1.5   | Max. capacity                                                   | Q         | 1500 kg                  |
| 1.6   | Load center of gravity                                          | c         | 500 mm                   |
| 1.8   | Load distance, centre of drive axle to fork                     | x         | 365 mm                   |
| 1.9   | Wheelbase                                                       | y         | 1220 mm                  |
|       | <b>Weight</b>                                                   |           |                          |
| 2.1   | Service weight                                                  |           | 3000 kg                  |
| 2.2   | Weight on front axle (laden) / rear axle (laden)                |           | 3930 kg / 570 kg         |
| 2.3   | Weight on front axle (Unladen) / rear axle (Unladen)            |           | 1370 kg / 1630 kg        |
|       | <b>Wheels</b>                                                   |           |                          |
| 3.1   | Tires type                                                      |           | Super Elastic            |
| 3.2   | Dimensions of front wheels                                      |           | 18x7-8                   |
| 3.3   | Dimensions of rear wheels                                       |           | 200/50-10                |
| 3.5   | Number of front wheels / rear wheels                            |           | 2 / 1                    |
| 3.5.2 | Number of drive wheels                                          |           | 1                        |
| 3.6   | Front wheel gauge                                               | b10       | 835 mm                   |
|       | <b>Dimensions</b>                                               |           |                          |
| 4.7   | Height of overhead guard (cabin)                                | h6        | 2105 mm                  |
| 4.8   | Seat height/stand height                                        | h7        | 1020 mm                  |
| 4.12  | Height of towing bar (coupling height)                          | h10       | 500 mm                   |
| 4.19  | Overall length                                                  | l1        | 3015 mm                  |
| 4.20  | Length to face of forks                                         | l2        | 1865 mm                  |
| 4.21  | Overall width                                                   | b1        | 990 mm                   |
| 4.22  | Forks section / width / length                                  | s / e / l | 35 mm x 100 mm x 1150 mm |
| 4.23  | Fork carriage ISO 2328 (class/form) A/B                         |           | 2A                       |
| 4.24  | Fork carriage width                                             | b3        | 1000 mm                  |
| 4.31  | Ground clearance below mast                                     | m1        | 100 mm                   |
| 4.32  | Ground clearance at centre of wheelbase                         | m2        | 100 mm                   |
| 4.33  | Aisle Width for pallets 1000 x 1200 crossways                   | Ast       | 3201 mm                  |
| 4.34  | Aisle width for 800 x 1200 pallet lengthways                    | Ast       | 3325 mm                  |
| 4.35  | Turning radius                                                  | Wa        | 1510 mm                  |
|       | <b>Performances</b>                                             |           |                          |
| 5.1   | Travel speed (laden / unladen)                                  |           | 9.50 km/h/10.50 km/h     |
| 5.2   | Lifting speed (laden / unladen)                                 |           | 0.22 m/s-0.34 m/s        |
| 5.3   | Lowering speed (laden / unladen)                                |           | 0.58 m/s-0.48 m/s        |
| 5.5   | Drawbar pull (Laden / Unladen)                                  |           | 500 daN / 530 daN        |
| 5.7   | Gradeability (laden / unladen)                                  |           | 7 % / 9 %                |
| 5.10  | Service brake                                                   |           | Hydraulic                |
|       | <b>Engine</b>                                                   |           |                          |
| 6.1   | Drive motor rating S2 60 min                                    |           | 4 kW                     |
| 6.3   | Battery according to DIN 43531/35/36 A, B, C                    |           | DIN43535 A               |
| 6.4   | Battery voltage / capacity                                      |           | 24 V / 840 Ah            |
| 6.6   | Energy consumption                                              |           | 3.50 kWh                 |
| 7.2   | Engine power according to ISO 1585                              |           | 8.60 kW                  |
|       | <b>Miscellaneous</b>                                            |           |                          |
| 8.1   | Type of drive control                                           |           | Electric                 |
| 8.2   | Working hydraulic pressure for attachments                      |           | 145 bar                  |
| 8.3   | Oil flow rate for attachments                                   |           | 16 l/min                 |
| 8.4   | Measured/guaranteed mean noise level at the ear of the operator |           | < 70 dB                  |
| 8.4   | Sound level at the driver's ear according to DIN 12 053         |           | 40 dB                    |

## ME 315 C - Maßzeichnung



Technische Daten und Resttragfähigkeiten der Hubgerüste

| Full Visibility Duplex (FVD)                              |    | FVD 27 | FVD 30 | FVD 33 | FVD 36 | FVD 40 | FVD 43 | FVD 45 |
|-----------------------------------------------------------|----|--------|--------|--------|--------|--------|--------|--------|
| Mast/fork carriage tilt, forward                          | °  | 6      | 6      | 6      | 6      | 3.50   | 3.50   | 3.50   |
| Mast/fork carriage tilt, backward                         | °  | 5      | 5      | 5      | 5      | 5      | 5      | 5      |
| h1 - Mast lowered height                                  | mm | 1830   | 1980   | 2130   | 2330   | 2580   | 2730   | 2830   |
| h2 - Mast free lift                                       | mm | 155    | 155    | 155    | 155    | 155    | 155    | 155    |
| h3 - Mast lifting height                                  | mm | 2700   | 3000   | 3300   | 3600   | 4000   | 4300   | 4500   |
| h4 - Mast extended height                                 | mm | 3233   | 3533   | 3833   | 4133   | 4533   | 4833   | 5033   |
| Residual capacity at max height                           | kg | 1500   | 1500   | 1500   | 1500   | 1500   | 1500   | 1450   |
| Residual capacity with integrated side shift at max heigh | kg | 1500   | 1500   | 1500   | 1500   | 1500   | 1500   | 1450   |
| Residual capacity with hooked-on side shift at max heigh  | kg | 1500   | 1500   | 1500   | 1500   | 1450   | 1400   | 1350   |
| Height at max capacity                                    | mm | 2700   | 3000   | 3300   | 3600   | 4000   | 4300   | 4000   |
| Height at max capacity with integrated sideshift          | mm | 2700   | 3000   | 3300   | 3600   | 4000   | 4300   | 4000   |

| Free Lift Duplex (FLD)                                    |    | FLD 27 | FLD 30 | FLD 33 | FLD 36 | FLD 40 |
|-----------------------------------------------------------|----|--------|--------|--------|--------|--------|
| Mast/fork carriage tilt, forward                          | °  | 6      | 6      | 6      | 6      | 3.50   |
| Mast/fork carriage tilt, backward                         | °  | 5      | 5      | 5      | 6      | 5      |
| h1 - Mast lowered height                                  | mm | 1845   | 1995   | 2145   | 2295   | 2545   |
| h2 - Mast free lift                                       | mm | 1286   | 1436   | 1586   | 1736   | 1986   |
| h3 - Mast lifting height                                  | mm | 2700   | 3000   | 3300   | 3600   | 4000   |
| h4 - Mast extended height                                 | mm | 3259   | 3559   | 3859   | 4159   | 4559   |
| Residual capacity at max height                           | kg | 1500   | 1500   | 1500   | 1500   | 1500   |
| Residual capacity with integrated side shift at max heigh | kg | 1500   | 1500   | 1500   | 1500   | 1500   |
| Residual capacity with hooked-on side shift at max heigh  | kg | 1500   | 1500   | 1500   | 1500   | 1450   |
| Height at max capacity                                    | mm | 2700   | 3000   | 3300   | 3600   | 4000   |
| Height at max capacity with integrated sideshift          | mm | 2700   | 3000   | 3300   | 3600   | 4000   |

| Free Lift Triplex (FLT)                                   |    | FLT 40 | FLT 43 | FLT 45 | FLT 48 | FLT 50 | FLT 55 | FLT 60 | FLT 65 |
|-----------------------------------------------------------|----|--------|--------|--------|--------|--------|--------|--------|--------|
| Mast/fork carriage tilt, forward                          | °  | 3.50   | 3.50   | 3.50   | 3.50   | 3.50   | 3.50   | 3.50   | 3.50   |
| Mast/fork carriage tilt, backward                         | °  | 5      | 5      | 5      | 5      | 5      | 5      | 5      | 5      |
| h1 - Mast lowered height                                  | mm | 1945   | 2045   | 2095   | 2245   | 2345   | 2545   | 2795   | 2995   |
| h2 - Mast free lift                                       | mm | 1371   | 1471   | 1521   | 1671   | 1771   | 1971   | 2200   | 2400   |
| h3 - Mast lifting height                                  | mm | 4000   | 4300   | 4500   | 4800   | 5000   | 5500   | 6000   | 6500   |
| h4 - Mast extended height                                 | mm | 4584   | 4884   | 5084   | 5384   | 5584   | 6084   | 6605   | 7105   |
| Residual capacity at max height                           | kg | 1450   | 1400   | 1350   | 1300   | 1250   | 1200   | 1000   | 600    |
| Residual capacity with integrated side shift at max heigh | kg | 1450   | 1400   | 1350   | 1300   | 1250   | 1200   | 1000   | 600    |
| Residual capacity with hooked-on side shift at max heigh  | kg | 1350   | 1300   | 1250   | 1200   | 1150   | 1100   | 900    | 500    |
| Height at max capacity                                    | mm | 2500   | 4300   | 2500   | 2500   | 2500   | 2500   | 2500   | 2500   |



#### Hauptsitz

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



Diese Publikation enthält eine Beschreibung der Konfigurationsvarianten und Optionen für Manitou-Produkte, die je nach Ausstattung unterschiedlich sein können. Die in dieser Broschüre vorgestellten Ausstattungen können Teil einer Serie, als Option erhältlich oder je nach Ausführung nicht verfügbar sein. Manitou behält sich das Recht vor, die beschriebenen und dargestellten Spezifikationen jederzeit und ohne Vorankündigung zu ändern. Die angegebenen Spezifikationen sind für den Hersteller nicht bindend. Für weitere Einzelheiten wenden Sie sich bitte an Ihren Manitou-Händler. Es handelt sich nicht um ein vertraglich bindendes Dokument. Die Darstellung der Produkte ist vertraglich nicht bindend. Die Liste der Spezifikationen ist nicht vollständig. Die Logos sowie die visuelle Identität des Unternehmens sind Eigentum von Manitou und dürfen nicht ohne Genehmigung verwendet werden. Alle Rechte vorbehalten. Die in dieser Broschüre enthaltenen Fotos und Diagramme werden nur zu Anschauungs- und Informationszwecken zur Verfügung gestellt.

MANITOU BF SA - Gesellschaft mit beschränkter Haftung mit Verwaltungsrat - Aktienkapital: 39 668 399 Euro - 857 802 508 RCS Nantes