

Technische fiche :

# **ES 612 LI (5PTS)**

---



 **MANITOU**  
HANDLING YOUR WORLD

Technical characteristics			Metrisch	
1.1	Manufacturer		Manitou	
1.2	Model Name		ES 612 LI 5 points	
1.3	Power source		Electrical	
1.4	Operator type		Pedestrian	
1.5	Max. capacity	Q	1200 kg	
1.6	Load center of gravity	c	600 mm	
1.8	Distance from Load backrest to center of rear axle	x	834 mm	
1.9	Wheelbase	y	1492 mm	
Weight				
2.1	Service weight		1251 kg	
2.2	Weight on front axle (laden) / rear axle (laden)		1295 kg / 1163 kg	
2.3	Weight on front axle (Unladen) / rear axle (Unladen)		1328 kg / 1003 kg	
Wheels				
3.1	Tires type		Bandage	
3.3	Number of load wheels / Size of load wheels		2 / 140x60	
3.4	Number of stabilizer wheels / Size of the stabilizer wheels		1 / 140x60	
3.5	Number of front wheels / rear wheels		3 / 4	
3.5.2	Number of drive wheels / Size of drive wheels		1/230x70	
3.6	Front wheel gauge	b10	529 mm	
3.7	Rear wheel gauge	b11	380 mm	
Dimensions				
4.6	Initial lift	h5	110 mm	
4.19	Overall length	l1	2162 mm	
4.20	Length to face of forks	l2	973 mm	
4.21	Overall width	b1	800 mm	
4.22	Forks section / width / length	s / e / l	60 mm / 185 mm / 1190 mm	
4.24	Fork carriage width	b3	700 mm	
4.32	Ground clearance at centre of wheelbase	m2	30 mm	
4.33	Aisle Width for pallets 1000 x 1200 crossways	Ast	2398 mm	
4.34	Aisle width for 800 x 1200 pallet lengthways	Ast	2394 mm	
4.35	Turning radius	Wa	1849 mm	
4.9	Height tiller min. / max.	h14 / h14	750 mm / 1250 mm	
Performances				
5.1	Travel speed (laden / unladen)		4.50 km/h / 4.50 km/h	
5.2	Lifting speed (laden / unladen)		0.18 m/s / 0.30 m/s	
5.3	Lowering speed (laden / unladen)		0.27 m/s / 0.22 m/s	
5.8	Max Gradeability (laden / unladen)		7 % / 10 %	
5.10	Service brake		Electro magnetic	
Engine				
6.1	Drive motor rating S2 60 min		1.50 kW	
6.2	Lift motor rating at S3 15%		3 kW	
6.3	Battery according to DIN 43531/35/36 A, B, C		DIN 43535-B	
6.4	Battery voltage / capacity		24 V / 180 Ah	
6.5	Battery weight (+/- 5%)		189 kg	
Miscellaneous				
8.1	Type of drive control		AC	
8.4	Sound level at the driver's ear according to DIN 12 053		65 dB	

ES 612 LI (5pts) - Tekening met afmetingen



## Kenmerken van de masten en restcapaciteiten

Central Cylinder Simplex (CCS)		CCS 15	CCS 17
h1 - Mast lowered height	mm	1953	2203
h2 - Mast free lift	mm	1506	1756
h3 - Mast lifting height	mm	1506	1756
h4 - Mast extended height	mm	1960	2210
Residual capacity at max height	kg	1200	1200

Free Lift Duplex (FLD)		FLD 29	FLD 34
h1 - Mast lowered height	mm	1953	2203
h2 - Mast free lift	mm	1506	1756
h3 - Mast lifting height	mm	2931	3431
h4 - Mast extended height	mm	3385	3885
Residual capacity at max height	kg	1200	900

Free Lift Triplex (FLT)		FLT 42
h1 - Mast lowered height	mm	1911
h2 - Mast free lift	mm	1466
h3 - Mast lifting height	mm	4246
h4 - Mast extended height	mm	4723
Residual capacity at max height	kg	550



**Hoofdkantoor**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - Frankrijk

Tel.: 00 33 (0)2 40 09 10 11 - Fax: 00 33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



Deze brochure beschrijft versies en configuratie-opties voor Manitou-producten die met verschillende apparatuur kunnen worden uitgerust. De uitrusting die in deze brochure wordt beschreven, kan standaard, optioneel of niet leverbaar zijn, afhankelijk van de uitvoering. Manitou behoudt zich het recht voor om de weergegeven en beschreven specificaties op elk moment en zonder kennisgeving vooraf te wijzigen. De fabrikant is niet aansprakelijk voor de gegeven specificaties. Neem voor meer informatie contact op met uw Manitou-dealer. Niet-contractueel document. De productbeschrijvingen kunnen afwijken van de werkelijke producten. De lijst met specificaties is niet allesomvattend. De logo's en visuele identiteit van het bedrijf zijn eigendom van Manitou en mogen niet zonder toestemming worden gebruikt. Alle rechten voorbehouden. De foto's en diagrammen in deze brochure zijn uitsluitend bedoeld voor raadpleging en informatie.

MANITOU BF SA - Naamloze vennootschap met raad van bestuur - Aandeelkapitaal: 39.668.399 euro - 857 802 508 RCS Nantes