Technical sheet:

MT 420 H






	MT 420 H Created on November 8, 2025 at 8:	.25 PM UT
Capacities	Metric	
Max. capacity	2000 kg	
Max. lifting height	4.35 m	
Maximum outreach	2.65 m	
Breakout force with bucket	1886 daN	
Weight and dimensions	1000 dail	
Overall length to carriage	l11 3.64 m	
Length to face of forks	12 3.58 m	
Overall width	b1 1.49 m	
Overall height	h17 1.97 m	
•		
Wheelbase	y 2.13 m	
Ground clearance	m4 0.24 m	
Overall cab width	b4 0.80 m	
Tilt-up angle	a4 12 °	
Tilt-down angle	a5 116°	
External turning radius (over tyres)	Wa1 2.98 m	
Unladen weight (with forks)	4190 kg	
Overall weight	4260 kg	
Tires type	Inflatable	
Forks length / width / section	I / e / s 1200 mm x 125 mm x 45 m	ım
Performances		
Lifting	5 s	
Lowering	3.50 s	
Extension	4.80 s	
Retraction	3 s	
Crowd	3.30 s	
Dump	2.70 s	
Engine	2.700	
Engine brand	Kubota	
Engine norm	Stage V	
	2607-CR-E5	
Engine model		
Number of cylinders / Capacity of cylinders	4 - 2615 cm³	
Engine power (Hp/kW)	57 Hp / 42 kW	
Max. torque / Engine rotation	174 Nm @ 1600 rpm	
Drawbar pull (Laden)	2850 daN	
Transmission		
Transmission type	Hydrostatic	
Number of gears (forward / reverse)	2/2	
Max. travel speed	24.90 km/h	
Max. travel speed (may vary according to applicable regulations)	24.90 km/h	
Parking brake	Automatic Negative Hand-bra	ake
Service brake	Disk brake on the cadran sh	ıaft
Hydraulics		
Hydraulic pump type	Gear pump	
Hydraulic flow / Pressure	77.40 l/min-235 bar	
Tank capacities		
Engine oil	10.20	
Hydraulic oil	701	
Hydraulic tank capacity	10.20	
Fuel	60 1	
Noise and vibration	60 I	
Noise and vibration Noise at driving position (LpA)	76 10	
, , , ,	76 dB	
Noise to environment (LwA)	104 dB	
Vibration on hands/arms	< 2.50 m/s ²	
Miscellaneous		
Steering wheels (front / rear)	2/2	
Drive wheels (front / rear)	2/2	
Safety / Cab certification	Standard EN 15000 / ROPS - FOPS ca	ab (level 1)
Controls	JSM	


MT 420 H - Dimensional drawing





MT 420 H - Load chart

Machine on tires with forks Metric







Head Office

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes