

Technical sheet :

ATJ 46




Capacities		Imperial
Working height	h21	52 ft 6 in
Platform height	h7	46 ft
Max. outreach		27 ft 3 in
Overhang		24 ft 7 in
Pendular arm rotation (top / bottom)		+65 ° / -59.50 °
Platform capacity	Q	500 lb
Turret rotation		350 °
Platform rotation (right / left)		90 ° / 90 °
Number of people (indoor / outdoor)		2 / 2
Weight and dimensions		
Platform weight*		13426 lb
Platform dimensions (length x width)	lp / ep	6 ft 11 in x 2 ft 7 in
Floor height (access)	h20	1 ft 4 in
Overall length	l1	21 ft 11 in
Overall width	b1	7 ft 7 in
Overall height	h17	7 ft 9 in
Overall length (stowed)	l9	14 ft 9 in
Overall height (stowed)	h18 ***	9 ft 3 in
Counterweight offset (turret at 90°)	a7	9 in
Counterweight Oversize / Reach		9 in
External turning radius	Wa3	17 ft
Ground clearance at centre of wheelbase	m2	1 ft 2 in
Wheelbase	y	7 ft 3 in
Performances		
Drive speed - stowed		3 mph
Drive speed - raised		0.62 mph
Gradeability		45 %
Wheels		
Tires type		Foam-filled
Standard tires		834 x 298 mm
Drive wheels (front / rear)		2 / 2
Steering wheels (front / rear)		2 / 0
Braking wheels (front / rear)		0 / 2
Engine/Battery		
Engine brand / model		Kubota - D1105-E4B
Engine nom		Interim Tier 4, Stage IIIA, Stage V
Engine power (Hp / kW)		24.80 Hp / 18.50 kW
Miscellaneous		
Ground Pressure		139 PSI
Hydraulic Pressure		4931 PSI
Hydraulic tank capacity		14 US gal
Fuel tank capacity		14 US gal
Noise to environment (LWA)		< 105 dB
Vibration on hands/arms		< 2 ft/s²
Daily consumption **		1 US gal
Standards compliance		
This machine is in compliance with:		ANSI A92.20-2018 CSA B354.6 ICES-002-Issue 6 Standard Canadian EMC

*Varies according to options and standards of the country to which the machine is delivered

ATJ 46 - Load chart

Load Chart for MEWP (Imperial)



ATJ 46 - Dimensional drawing



Equipment

Standard

4 simultaneous movements
4 wheel drive
Audible alarm and illuminated indicator lamp (leveling, overload, lowering)
Basket 1,800 mm
Basket controls protection
Battery cut-off
CAN bus technology
Cumulative lifting and driving functions
Diesel tank locking cap
Differential locking on rear axle
Driver presence pedal
Easy Manager
Electric plug - 110V - In the basket - With differential circuit breaker - USA (B) type
Emergency stop button in platform and on frame
Engine pre-heater
Flat Led Rotating Beacon
Front axle with limited slip
Fuel gauge with low level indicator
Fully galvanized basket with removable floor - Width: 2100 mm (6 ft. 11 in.)
Integrated diagnostic assistance
Management via engine speed bearing
Pendular arm
Proportional controls
Side swing gate
Simultaneous steering and turret rotation functions
Turret orientation detector

Optional

Biodegradable oil
Cold environment package
Cold weather protection oil
Foam filled tyres
Key lock on turret cover
LED work light - On basket
On-board generator (3,5 or 5 kW)
Secondary Protection System (SPS)
Turret orientation detector
Water pre-fitting

**Head Office**

B.P. 249 - 430 rue de l'Aubinière
44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes