Technical sheet:

280 TJ-X







	280 TJ-X UTG	ated on November 5, 2025 at 3:56 AM UTC
Capacities		Metric
Working height	h21	27.73 m
Platform height	h7	25.73 m
Maximum outreach		21.45 m
Pendular arm rotation (top / bottom)		+56.80 ° / -62 °
Platform capacity / capacity (maximum)	Q	240 kg / 350 kg
Turret rotation		360 °
Platform rotation (right / left)		90 ° / 90 °
Number of people (indoor / outdoor)		2/3
Weight and dimensions		
Platform weight*		16650 kg
Platform dimensions (length x width)	lp / ep	2.30 m x 0.90 m
Floor height (access)	h20	0.48 m
Overall length	l1	11.36 m
Overall width	b1	2.48 m
Overall height	h17	2.73 m
Overall length (stowed)	19	8.09 m
Overall height (stowed)	h18 ***	2.71 m
Overall length with platform extension	l15	11.35 m
Counterweight Oversize / Reach		1.45 m
Ground clearance at centre of wheelbase	m2	0.41 m
Wheelbase	٧	2.80 m
Performances		
Drive speed - stowed		4.50 km/h
Drive speed - raised		0.80 km/h
Gradeability		34 %
Permissible leveling		4 °
Wheels		
Drive wheels (front / rear)		2 / 2
Braking wheels (front / rear)		2/2
Engine/Battery		
Engine brand / model		Kubota - V2403-M
Engine norm		Tier 4
Engine power (Hp / kW)		46 Hp / 34.10 kW
Miscellaneous		101197 01110 1011
Ground Pressure		22.25 dan/cm2
Hydraulic Pressure		250 bar
Fuel		72
Vibration on hands/arms		< 0.50 m/s ²
Daily consumption **		10.81
Standards compliance		13.011
		European directives: 2006/42/EC- Machinery
This machine is in compliance with:		(revised EN280:2013) - 2004/108/EC (EMC)

280 TJ-X - Load chart

Load Chart for MEWP Metric



280 TJ-X - Dimensional drawing



Equipment

Standard	
20" tyres	
230V Predisposition	
4 simultaneous movements	
4 wheel drive	
4 wheel steer with crab mode	
Audible alarm and illuminated indicator lamp (leveling, overload, lowering)	
Backup electrical pump	
CAN bus technology	
Continuous turret rotation	
Dead man pedal	
Differential locking on rear axle	
Electronic platform compensation	
Emergency stop button in platform and on frame	
Engine on swivel chair	
Front axle with limited slip	
Fuel gauge with low level indicator	
Hom in the platform	
Integrated diagnostic assistance	
Oscillating front axle	
Painted basket for heavy loads 2,300 mm (7ft 7 in.)	

Optional
110 or 230V plug with differential circuit breaker
Additional storage boxes
Basket 1,800 mm
Biodegradable oil
Catalytic cleaner
Coded anti-start
Cold weather protection oil
Engine compartment with key lock
High capacity starting battery
Lockable fuel cap
Non-marking thres
On-board generator (3,5 or 5 kW)
Refinery kit
SMS : Safe Man System
Safety hamess
Screen protection on the lower box control
Water predisposition





Head Office

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes