Technical sheet:

200 ATJ-X






	200 ATJ-X Creat	ed on October 29, 2025 at 1:23 AM UTO
Capacities		Metric
Working height	h21	20.28 m
Platform height	h7	18.28 m
Maximum outreach		12 m
Overhang		8 m
Pendular arm rotation (top / bottom)		+69 ° / -66 °
Platform capacity	Q	230 kg
Turret rotation		355 °
Platform rotation (right / left)		90 ° / 90 °
Number of people (indoor / outdoor)		2 / 2
Weight and dimensions		
Platform weight*		10050 kg
Platform dimensions (length x width)	lp / ep	2.10 m x 0.80 m
Floor height (access)	h20	0.51 m
Overall length	I1	8.42 m
Overall width	b1	2.40 m
Overall height	h17	2.71 m
Overall length (stowed)	19	6.21 m
Overall height (stowed)	h18 ***	2.85 m
Counterweight offset (turret at 90Ű)	a7	0.11 m
Counterweight Oversize / Reach	u,	0.11 m
External turning radius	Wa3	4.17 m
Ground clearance at centre of wheelbase	m2	0.44 m
Wheelbase	y	2.40 m
Performances		2.40 111
Drive speed - stowed		4.70 km/h
Drive speed - raised		0.80 km/h
Gradeability		40 %
Permissible leveling		5 °
Wheels		Ü
Tires type		Solid tires
Standard tires		1025 x 365 mm
Drive wheels (front / rear)		2 / 2
Steering wheels (front / rear)		2/2
Braking wheels (front / rear)		0 / 2
Engine/Battery		0 / 2
Engine brand / model		Kubota - V2403-M
Engine norm		Stage IIIA
Engine power (Hp / kW)		46 Hp / 34.10 kW
Miscellaneous		40 Hp / 34.10 KW
Ground Pressure		20.65 dan/cm2
Hydraulic Pressure		335 bar
•		80 l
Hydraulic tank capacity Fuel tank		78 I
		/8 I < 0.50 m/s²
Vibration on hands/arms		
Daily consumption **		7.96 l
Standards compliance		Furnament directions 2006 (40 /FO Marchi
This machine is in compliance with:		European directives: 2006/42/EC- Machinery (revised EN280:2013) - 2004/108/EC (EMC)
		. ,


^{*}Varies according to options and standards of the country to which the machine is delivered ** According to "REDUCE cycle" $\,$


200 ATJ-X - Load chart


Load Chart metric



200 ATJ-X - Dimensional drawing







Equipment

Standard 230V Predisposition 4 simultaneous movements 4 wheel drive 4 wheel steer with crab mode Audible alarm and illuminated indicator lamp (leveling, overload, lowering) Backup electrical pump CAN bus technology Dead man pedal Differential locking on rear axle Fuel gauge with low level indicator Galvanized basket 2,100 mm Hour meter Management via engine speed bearing Oscillating front axle Proportional controls

Optional
110 or 230V plug with differential circuit breaker
Battery cut-off
Biodegradable oil
Catalytic cleaner
Coded anti-start
Cold weather protection oil
Continuous turret rotation
Engine compartment with key lock
High capacity starting battery
Key lock on fuel tank
On-board generator (3,5 or 5 kW)
SMS : Safe Man System
Safety hamess
Screen protection on the lower box control
Spark arrester
Water heater
Working light





Head Office

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes