

Technical sheet :

# 200 ATJ-X



 **MANITOU**  
HANDLING YOUR WORLD

| Capacities                              |         | Metric   |
|---|---------|--|
| Working height                          | h21     | 20.28 m  |
| Floor height (access)                   | h20     | 0.51 m   |
| Platform height                         | h7      | 18.28 m  |
| Max. outreach                           |         | 12 m   |
| Overhang                                |         | 8 m  |
| Pendular arm rotation (top / bottom)    |         | +69 ° / -66 °  |
| Platform capacity                       | Q       | 230 kg   |
| Turret rotation                         |         | 355 °  |
| Platform rotation (right / left)        |         | 90 ° / 90 °  |
| Number of people (indoor / outdoor)     |         | 2 / 2  |
| Weight and dimensions                   |         |  |
| Platform weight*                        |         | 10050 kg   |
| Platform dimensions (length x width)    | lp / ep | 2.10 m x 0.80 m  |
| Overall length                          | l1      | 8.42 m   |
| Overall width                           | b1      | 2.40 m   |
| Overall height                          | h17     | 2.71 m   |
| Overall length (stowed)                 | l9      | 6.21 m   |
| Overall height (stowed)                 | h18     | 2.85 m   |
| Counterweight offset (turret at 90°)    | a7      | 0.11 m   |
| Counterweight Oversize / Reach          |         | 0.11 m   |
| External turning radius                 | Wa3     | 4.17 m   |
| Ground clearance at centre of wheelbase | m2      | 0.44 m   |
| Wheelbase                               | y       | 2.40 m   |
| Performances                            |         |  |
| Drive speed - stowed                    |         | 4.70 km/h  |
| Drive speed - raised                    |         | 0.80 km/h  |
| Gradeability                            |         | 40 %   |
| Permissible leveling                    |         | 5 °  |
| Wheels                                  |         |  |
| Tires type                              |         | Solid Tires Cured-On   |
| Standard tires                          |         | 1025 x 365 mm  |
| Drive wheels (front / rear)             |         | 2 / 2  |
| Steering wheels (front / rear)          |         | 2 / 2  |
| Braking wheels (front / rear)           |         | 0 / 2  |
| Engine/Battery                          |         |  |
| Engine brand / model                    |         | Kubota - V2403-M   |
| Engine norm                             |         | Stage IIIA   |
| I.C. Engine power rating / Power        |         | 46 Hp / 34.10 kW   |
| Miscellaneous                           |         |  |
| Ground Pressure                         |         | 20.65 dan/cm2  |
| Hydraulic Pressure                      |         | 335 bar  |
| Hydraulic tank capacity                 |         | 80 l   |
| Fuel tank                               |         | 78 l   |
| Vibration on hands/arms                 |         | < 0.50 m/s²  |
| Daily consumption **                    |         | 7.96 l   |
| Standards compliance                    |         |  |
| This machine is in compliance with:     |         | European directives: 2006/42/EC- Machinery (revised EN280:2013) - 2004/108/EC (EMC) - 2006/95/EC (Low voltage) |

\*Varies according to options and standards of the country to which the machine is delivered

\*\* According to "REDUCE cycle"

200 ATJ-X - Load chart

Load Chart metric



200 ATJ-X - Dimensional drawing



# Equipment

| Standard  |
|---|
| 230V Predisposition   |
| 4 simultaneous movements  |
| 4 wheel drive   |
| 4 wheel steer with crab mode  |
| Audible alarm and illuminated indicator lamp (leveling, overload, lowering) |
| Backup electrical pump  |
| CAN bus technology  |
| Dead man pedal  |
| Differential locking on rear axle   |
| Fuel gauge with low level indicator   |
| Galvanized basket 2,100 mm  |
| Hour meter  |
| Management via engine speed bearing   |
| Oscillating front axle  |
| Proportional controls   |
| Rear axle with limited slip differential                                    |

| Optional   |
|--|
| 110 or 230V plug with differential circuit breaker |
| Battery cut-off                                    |
| Biodegradable oil                                  |
| Catalytic cleaner                                  |
| Coded anti-start                                   |
| Cold weather protection oil                        |
| Continuous turret rotation                         |
| Highly capacity battery                            |
| Key lock on fuel tank                              |
| Key lock on turret cover                           |
| On-board generator (3,5 or 5 kW)                   |
| SMS : Safe Man System                              |
| Safety harness                                     |
| Screen protection on the lower box control         |
| Spark arrester                                     |
| Water heater                                       |
| Working light                                      |



**Head Office**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes