

Technical sheet :

220 TJ-XP



 **MANITOU**
HANDLING YOUR WORLD

| Capacities | | Metric |
|---|---------|---|
| Working height | h21 | 21.74 m |
| Platform height | h7 | 19.74 m |
| Maximum outreach | | 17.78 m |
| Pendular arm rotation (top / bottom) | | +70 ° / -63 ° |
| Platform capacity | Q | 350 kg |
| Turret rotation | | 360 ° |
| Platform rotation (right / left) | | 90 ° / 90 ° |
| Number of people (indoor / outdoor) | | 3 / 3 |
| Weight and dimensions | | |
| Platform weight* | | 13600 kg |
| Platform dimensions (length x width) | lp / ep | 2.30 m x 0.90 m |
| Floor height (access) | h20 | 0.39 m |
| Overall length | l1 | 10.05 m |
| Overall width | b1 | 2.48 m |
| Overall height | h17 | 2.52 m |
| Overall length (stowed) | l9 | 7.35 m |
| Overall height (stowed) | h18 *** | 3.03 m |
| Jib length | l13 | 2 m |
| Counterweight Oversize / Reach | | 1.34 m |
| External turning radius | Wa3 | 4.40 m |
| Ground clearance at centre of wheelbase | m2 | 0.44 m |
| Wheelbase | y | 2.80 m |
| Performances | | |
| Drive speed - stowed | | 5.40 km/h |
| Drive speed - raised | | 1 km/h |
| Gradeability | | 40 % |
| Permissible leveling | | 4 ° |
| Wheels | | |
| Tires type | | Solid Tires Cured-On |
| Drive wheels (front / rear) | | 2 / 2 |
| Steering wheels (front / rear) | | 2 / 2 |
| Braking wheels (front / rear) | | 2 / 2 |
| Engine/Battery | | |
| Engine brand / model | | Kubota - V1505.E3B |
| Engine norm | | Stage IIIA |
| I.C. Engine power rating / Power | | 35 Hp / 26.20 kW |
| Miscellaneous | | |
| Ground Pressure | | 18.30 dan/cm2 |
| Hydraulic Pressure | | 400 bar |
| Hydraulic tank capacity | | 94 l |
| Fuel tank | | 72 l |
| Noise to environment (LwA) | | < 107 dB |
| Vibration on hands/arms | | < 0.50 m/s² |
| Daily consumption ** | | 7.98 l |
| Standards compliance | | |
| This machine is in compliance with: | | European directives: 2006/42/EC- Machinery (revised EN280:2013) - 2004/108/EC (EMC) |

*Varies according to options and standards of the country to which the machine is delivered

** According to "REDUCE cycle"

220 TJ-XP - Load chart

Load Chart for MEWP Metric



220 TJ-XP - Dimensional drawing



Equipment

| Standard |
|---|
| 230V Predisposition |
| 4 simultaneous movements |
| 4 wheel steer with crab mode |
| Audible alarm and illuminated indicator lamp (leveling, overload, lowering) |
| Backup electrical pump |
| Continuous turret rotation |
| Differential locking on rear axle |
| Electronic platform compensation |
| Emergency stop button in platform and on frame |
| Engine mounted on sliding platform |
| Fuel gauge with low level indicator |
| Integrated diagnostic assistance |
| Oscillating front axle |
| Painted basket for heavy loads 2,300 mm (7ft 7 in.) |
| Protective cover for control panel |
| Remote control for transport |

| Optional |
|--|
| 110 or 230V plug with differential circuit breaker |
| Additional storage boxes |
| Basket 1,800 mm |
| Battery cut-off |
| Biodegradable oil |
| Catalytic cleaner |
| Cold weather protection oil |
| Engine compartment with key lock |
| Key lock on fuel tank |
| On-board generator (3,5 or 5 kW) |
| Panel support kit |
| SMS : Safe Man System |
| Safety hamess |
| Screen protection on the lower box control |
| Spark arrester |
| Special color paints |
| Tube support kit |
| Water predisposition |
| Working light |



Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes