Technical sheet:

MT 1440 EASY ST5







	MT 1440 EASY STS Created on October 28, 2025 at 9:24 AM U
Capacities	Metric
Max. capacity	4000 kg
Max. lifting height	13.53 m
Maximum outreach	9.46 m
Breakout force with bucket	7400 daN
Weight and dimensions	
Overall length to carriage	l11 6.02 m
Length to face of forks	12 6.13 m
Overall width	b1 2.36 m
Overall height	h17 2.45 m
Wheelbase	y 3.07 m
Ground clearance	m4 0.37 m
Overall cab width	b4 0.89 m
Tilt-up angle	a4 12 °
Tilt-down angle	a5 114°
External turning radius (over tyres)	Wa1 3.94 m
Unladen weight (with forks)	10855 kg
Overall weight	10900 kg
Tires type	Inflatable
Standard tires	Alliance 400/80 - 24 - 162A8
Forks length / width / section	1/e/s 1200 mm x 125 mm x 50 mm
Performances	17 C 7 S 1200 Hill X 123 Hill X 30 Hill
Lifting	16 s
	12.40 s
Lowering	17.40 s
Extension Retraction	
	13 s
Crowd	4 s
Dump	4 s
Engine	Davita
Engine brand	Deutz
Engine norm	Stage V, Tier 4 final
Engine model	TD 3.6 L
Number of cylinders / Capacity of cylinders	4 - 3621 cm³
Engine power (Hp/kW)	75 Hp / 55.40 kW
Max. torque / Engine rotation	340 Nm @ 1600 rpm
Drawbar pull (Laden)	8320 daN
Transmission	
Transmission type	Torque converter
Number of gears (forward / reverse)	4 / 4
Max. travel speed	24.90 km/h
Max. travel speed (may vary according to applicable regulations)	25 km/h
Parking brake	Automatic parking brake
Service brake	Oil-immersed multi-discs braking on front & rear axles
Hydraulics	dxics
•	Gear pump
Hydraulic pump type	106 l/min-270 bar
Hydraulic flow / Pressure	Tuo I/IIIII-270 Dai
Tank capacities	7.50
Engine oil	7.50
Hydraulic oil	1351
Hydraulic tank capacity	101
Fuel tank	140 l
Noise and vibration	70.10
Noise at driving position (LpA)	79 dB
Noise to environment (LwA)	102 dB
Vibration on hands/arms	< 2.50 m/s²
Miscellaneous	
Steering wheels (front / rear)	2/2
Drive wheels (front / rear)	2/2
Safety / Cab certification	Standard EN 15000 / Cabin ROPS - FOPS level 2
Controls	JSM

MT 1440 easy ST5 - Dimensional drawing









MT 1440 easy ST5 - Load chart

Machine on tires with forks - with levelling device Metric



Machine on lowered stabilisers with forks Metric







Head Office

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes