

Technical sheet :




MHT 12330



 **MANITOU**
HANDLING YOUR WORLD


Capacities		Metric	
Max. capacity		c	33000 kg
Load center of gravity			1200 mm
Max. lifting height			11.92 m
Maximum outreach			6.60 m
Weight and dimensions			
Overall length		l1	10.77 m
Unladen weight (with forks)		m4	49000 kg
Ground clearance		y	0.59 m
Wheelbase		l2	4.90 m
Length to face of forks		b1	8.37 m
Overall width		h17	2.98 m
Overall height		b4	3.60 m
Overall cab width		a4	0.97 m
Tilt-up angle		a5	10 °
Tilt-down angle		Wa1	100 °
External turning radius (over tyres)		b15	7.42 m
Outer turning radius (with forks)		l / e / s	9.33 m
Forks length / width / section		a9	2400 mm x 110 mm x 250 mm
Frame leveling corrector			6 °
Wheels			
Standard tires			21.00 R35
Number of front wheels / rear wheels			2 / 2
Steering wheels (front / rear)			4 / 4
Drive wheels (front / rear)			2 / 2
Steering mode			2 wheel steer, 4 wheel steer, Crab mode
Engine			
Engine brand			Deutz
Engine norm			Stage V, Tier 4 final
Engine model			TCD 6.1 L6
Number of cylinders / Capacity of cylinders			6 - 6100 cm³
Engine power (Hp / kW)			245 Hp / 180 kW
Max. torque / Engine rotation			1000 Nm@1450 rpm
Engine cooling system			Water
Number of batteries			2
Battery voltage			12 V
Drawbar pull			28400 daN
Transmission			
Transmission type			Hydrostatic with Powershift
Number of gears (forward / reverse)			3 / 3
Max. travel speed			25 km/h
Parking brake			Automatic negative parking brake
Service brake			Oil-immersed multi-discs braking on front & rear axles
Gradeability (laden)			36 %
Hydraulics			
Hydraulic pump type			Variable displacement pump
Hydraulic flow - Pressure			310 l/min - 350 bar
Tank capacities			
Engine oil			21 l
Hydraulic oil			570 l
Fuel			600 l
Diesel Exhaust fluid (AdBlue® type)			32 l
Noise and vibration			
Noise to environment (LwA)			110 dB
Vibration on hands/arms			2.50 m/s²
Miscellaneous			
Cab certification			Cabin ROPS - FOPS level 2
Controls			JSM
Attachment recognition system (E-Reco)			Standard

MHT 12330 - Dimensional drawing




MHT 12330 - Load chart


Machine on tires with forks LC 1200 mm Metric



Machine on tires with hook 36000 kg (Metric)



Machine on tires with 3-hook jib 36000 kg (Metric)





MANITOU HANDLING YOUR WORLD

Head Office

B.P. 249 - 430 rue de l'Aubinière
44150 Ancenis Cedex - France
Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97
www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes