

Technical sheet :


MHT 12330



 **MANITOU**
HANDLING YOUR WORLD

| Capacities | | Imperial |
|---|-----------|--|
| Max. capacity | | 72753 lb |
| Load center of gravity | c | 47 in |
| Max. lifting height | | 39 ft 1 in |
| Max. outreach | | 21 ft 8 in |
| Weight and dimensions | | |
| Overall length | l1 | 35 ft 4 in |
| Unladen weight (with forks) | | 108027 lb |
| Ground clearance | m4 | 1 ft 11 in |
| Wheelbase | y | 16 ft 1 in |
| Length to face of forks | l2 | 27 ft 6 in |
| Overall width | b1 | 9 ft 9 in |
| Overall height | h17 | 11 ft 10 in |
| Overall cab width | b4 | 3 ft 2 in |
| Tilt-up angle | a4 | 10 ° |
| Tilt-down angle | a5 | 100 ° |
| External turning radius (over tyres) | Wa1 | 24 ft 4 in |
| Outer turning radius (with forks) | b15 | 30 ft 7 in |
| Forks length / width / section | l / e / s | 94 in x 4 in / 10 in |
| Frame leveling corrector | a9 | 6 ° |
| Wheels | | |
| Standard tires | | 21.00 R35 |
| Number of front wheels / rear wheels | | 2 / 2 |
| Steering wheels (front / rear) | | 4 / 4 |
| Drive wheels (front / rear) | | 2 / 2 |
| Steering mode | | 2 wheel steer, 4 wheel steer, Crab mode |
| Engine | | |
| Engine brand | | Deutz |
| Engine norm | | Stage V / Tier 4 final |
| Engine model | | TCD 6.1 L6 |
| Number of cylinders / Capacity of cylinders | | 6 - 372 in³ |
| I.C. Engine power rating / Power | | 245 Hp / 180 kW |
| Max. torque / Engine rotation | | 738 ft/lbs@1450 rpm |
| Engine cooling system | | Water |
| Number of batteries | | 2 |
| Battery voltage | | 12 V |
| Drawbar pull | | 28400 daN |
| Transmission | | |
| Transmission type | | Hydrostatic with Powershift |
| Number of gears (forward / reverse) | | 3 / 3 |
| Max. travel speed | | 16 mph |
| Parking brake | | Automatic negative parking brake |
| Service brake | | Oil-immersed multi-discs braking on front & rear axles |
| Gradeability (laden) | | 36 % |
| Hydraulics | | |
| Hydraulic pump type | | Variable displacement pump |
| Hydraulic flow - Pressure | | 82 US gpm - 5076 PSI |
| Tank capacities | | |
| Engine oil | | 6 US gal |
| Hydraulic oil | | 151 US gal |
| Fuel tank | | 159 US gal |
| Diesel Exhaust fluid (AdBlue® type) | | 8 US gal |
| Noise and vibration | | |
| Noise at driving position (LpA) | | 80 dB |
| Noise to environment (LwA) | | 107 dB |
| Vibration on hands/arms | | < 2.50 m/s² |
| Miscellaneous | | |
| Safety cab homologation | | Cabin ROPS - FOPS level 2 |
| Controls | | JSM |
| Attachment recognition system (E-Reco) | | Standard |

MHT 12330 - Dimensional drawing



Mining Specifications

MHT 12330



Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes