Technical sheet :









	Metric 612 kg
	612 kg
	-
	2200 kg
	1224 kg
	1224 Ky
, i i i i i i i i i i i i i i i i i i i	923 mm
у h27	3584 mm
	2794 mm
	1826 mm
	42 °
	2197 mm
	2952 mm
	528 mm
	29 °
	99 °
h30	853 mm
b1	1346 mm
e1	1562 mm
m4	211 mm
12	2314 mm
a2	29 °
b18	1758 mm
	10.70 km/h
	Hydrostatic
	10 x 16.5 - 10 PR HD
	Yanmar
	4TNV88
	BS-III
	49 Hp
	142 Nm / 1600 rpm
	Diesel
	4
	Water cooled
	12 V
	55 A
	3 kW
	190 bar
	63.40 l/min
	47
	30.30 1
	2.20
	7.60 l
	8.25 l 8.25 l
	h28 h17 a5 h29 116 r6 a13 a4 h30 b1 e1 m4 i2 a2

1340R - Dimensional drawing







Equipment

Lifting function	
All-Tach® Attachment Mounting System	Standard
Auxiliary Hydraulics	Standard
Lighting	
Work Lights - Front and Rear	Standard
Motorization/Power	
Engine Block Heater	Standard
Operator station	
Cabin Rops and fops level I	Standard
Hand/Foot Controls	Optional
Hom	Optional
Sound Reduction Material	Standard
Suspension Seat - Mechanical	Standard
T-Bar control	Standard
Other options	
Selectable Self-Leveling Hydraulic Lift Action 4	Optional
Pneumatics	
Camso Tyres Option	Optional
Secondary functions	
Full Instrumentation	Standard
Security	
Anti-Vandalism Protection	Standard
Back-Up Alarm	Optional
Hydraloc™ Safety System	Standard
Operator Restraint Bar	Standard



Head Office B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes