Technical sheet:


1340R






Copposition Metec Rate Operating Capacity 512 kg Unuladien weight 2200 kg Tipping capacity 1224 kg Weight and dimensions 9 Wheehbase y 923 mm Overall Operating Height - Fully Raised 1627 3584 mm Height to Heigh Faily Raised 1628 2794 mm Oweall Height to up of RIDTS 117 1825 mm Dump angle at Ith beight 6 42 * Dump neath - Full height 16 2952 mm Dump neath - Full height 6 528 mm Rollback As ground 313 29 * Rollback As ground fieight 34 39 * Seat to ground height 36 43 * Creaml with bus buck to 10 1346 mm 1346 mm Bucket Width 6 528 mm Bucket Width 6 1582 mm Overall width best buck to 10 1346 mm 1346 mm Bucket Width 6 1 1582 mm Overall weight - Less Bucket 10	<u> </u>		Manda
Unider weight 1220 kg 17pping capacity 1224 kg 17pping capacity 1224 kg 17pping capacity 1224 kg 17pping capacity 17pping capa			metric
19ping capacity 1224 kg 1224 k	Rated Operating Capacity		612 kg
Weight and dimensions y 923 mm Wheebase y 923 mm Overall Operating Height - Fully Raised h27 3584 mm Height to Hinge Pin - Fully Raised h28 2794 mm Overall Height to Jong FOPS h17 1826 mm Dump angle at full height a5 42° Dump height h29 2197 mm Overall Height with Ducket h16 2952 mm Dump reach - Full height f6 528 mm Bullback Angle at Full Height a6 528 mm Rollback Angle at Full Height a4 99° Seat to gound height h50 853 mm Overall widh less bucket b1 1346 mm Bucket Widh e1 1346 mm Ground cleannee m4 211 mm Overall idength - Less Bucket e2 2314 mm Overall length - Less Bucket l2 2314 mm Operature angle la 152 mm Clearance Radius - Front with Bucket l8 1758 mm Performances	Unladen weight		2200 kg
Wheelbase y 923 mm Oventil Openting Height: Fully Raised h27 3584 mm Height to Hinge Pin - Fully Raised h28 2794 mm Overall Height to bop of ROPS h17 1826 mm Dump angle at full Height h29 2137 mm Owerall length with bucket h29 2137 mm Owerall Height n6 528 mm Rollback at ground a13 29 ° Rollback Angle at Full Height a4 99 ° Seat to ground Height a4 99 ° Ground clearance m4 211 mm Overall Height a1 156 mm Ground Clearance m4 211 mm Clearance Radius - Front with Bucket 12 2314 mm Performances 10.70 km/h	Tipping capacity		1224 kg
Overall Operating Height - Fully Raised h.27 3584 mm Height to kinge Fin - Fully Raised h.28 2794 mm Overall Height to kinge Fin - Fully Raised h.28 2794 mm Overall Height to kop of ROPS h.17 1526 mm Dump pagle at Full Height h.29 2197 mm Overall Height with bucket h.6 528 mm Outlaged at Full Height a.4 99 ° Rollback Angle at Full Height a.4 99 ° Seat to ground height h.30 853 mm Overall width is subcet b.1 1346 mm Bucket Width e.1 1552 mm Ground clearance m.4 211 mm Overall leight - Less Bucket b.1 1346 mm Departure angle a.2 29 ° Clearance Radius - Front with Bucket b.18 1758 mm Performances b.18 1758 mm Travel speed (unladen) 10.70 km/h 10.70 km/h Wheels 10.70 km/h 10.70 km/h Transmission type Proper source Proper so	Weight and dimensions		
Overall Operating Height - Hully Raised h27 3584 mm Height to Hinge Pin - Fully Raised h28 2794 mm Overall Height to top of ROPS h17 1826 mm Dump angle at full height a5 42° Dump height h16 2952 mm Overall Height with bucket 116 2952 mm Dum pach - Full height d6 528 mm Rollback Angle at Full Height a4 99° Rollback Angle at Full Height a4 99° Seat to gound height b1 1346 mm Overall width is bucket b1 1346 mm Bucket Width e1 1562 mm Ground clearance m4 211 mm Overall length: Less Bucket 12 2314 mm Operature angle a2 29° Clearance Radius - Front with Bucket b1 10.70 km/h Taxes speed (unladen) b1 10.70 km/h Wheels 10.70 km/h 10.70 km/h Taxes speed (unladen) 4 4 Bengine brand	Wheelbase	у	923 mm
Overall Height to top of ROPS h17 1826 mm Dump angle at full height a5 42* Dump angle at full height h29 2197 mm Overall length with bucket l16 2952 mm Dump reach - Full height n6 528 mm Rollback at ground a13 29 * Rollback Angle at Full Height a4 99 * Seat to ground height h30 853 mm Overall Height be subcet b1 1346 mm Bucket Width e1 1562 mm Ground clearance m4 211 mm Overall length - Less Bucket l2 2314 mm Operature angle a2 29 * Clearance Radius - Front with Bucket l2 2314 mm Performances l2 29 * Travel speed (unladen) l5 1758 mm Wheels l1758 mm Hydrostatic Sandard tires l10 x 165 - 10 PR HD 10 x 165 - 10 PR HD Engine brand l1 x 17 km 14 x 17 km 14 x 17 km Engine	Overall Operating Height - Fully Raised		3584 mm
Overall Height to top of ROPS h17 1826 mm Dump angle at ful height a5 42° Dump height h29 2197 mm Overall Length with bucket l16 2952 mm Dump reach - Full height a13 20° Rollback at ground a13 20° Rollback Angle at Full Height a4 99° Seat to ground height h30 853 mm Overall width less bucket h1 1346 mm Bucket Width e1 1562 mm Ground clearance e1 1562 mm Ground clearance e1 1562 mm Ground clearance angle a2 29° Clearance Radius - Front with Bucket b18 1758 mm Performances 12 2314 mm Performances 1 10 x 165 - 10 PR HD Transmission type Hydrostatic Standard tires 10 x 165 - 10 PR HD Engine brand 4 4 Engine model 4 4 Engine brown 142 Nm	Height to Hinge Pin - Fully Raised	h28	2794 mm
Dump angle at full height a5 42° Dump height h29 2197 mm Overall length with bucket 116 2952 mm Dump reach - Full height r6 528 mm Rollback At ground a13 29° Rollback At ground Full Height a4 99° Seat to ground height h30 853 mm Overall with less bucket b1 1346 mm Bucket Widh e1 1562 mm Ground clearance m4 211 mm Overall length - Less Bucket 12 2314 mm Overall length - Less Bucket 12 2314 mm Overall length - Less Bucket 12 2314 mm Overal length - Less Bucket 12 2314 mm Overall length - Less Bucket 12 2314 mm Overal length - Less Bucket 12 2314 mm Overal length - Less Bucket 18 1758 mm Plegrature angle 2 2° 2° Clearance Radius - Front with Bucket 3 1705 km/h Tawers ana		h17	1826 mm
Dump height h29 2197 mm Overall length with bucket 116 2952 mm Dump reach - Full height 6 528 mm Rollback at ground a13 29° Rollback Angle at Full Height h30 853 mm Overall width less bucket h30 853 mm Overall width less bucket b1 1346 mm Bucket Width e1 1562 mm Ground clearance m4 211 mm Overall length - Less Bucket 12 2314 mm Departure engle a2 29° Clearance Radius - Front with Bucket b18 1758 mm Performances Travel speed (unladen) 9 10,70 km/h Wheels 10,70 km/h Travel speed (unladen) 9 10,70 km/h Wheels 10,70 km/h Travel speed (unladen) 9 10,70 km/h Wheels 10,70 km/h 10,70 km/h Wheels 10,70 km/h 10,70 km/h <		a5	
Overall length with bucket 116 2952 mm Dump reach - Full height f6 528 mm Rollback at ground a13 29 ° Rollback Angle at Full Height a4 99 ° Seat to ground height h30 853 mm Overall width less bucket b1 1364 mm Bucket Width e1 1562 mm Ground clearance m4 211 mm Ground clearance m4 211 mm Overall leight - Less Bucket 12 2314 mm Departure angle a2 29 ° Clearance Radius - Front with Bucket b18 1758 mm Performances b18 1758 mm Travel speed (unladen) 10.70 km/h 10.70 km/h Wheels 10.70 km/h 10.70 km/h Engine brand Yanmar 10.70 km/h Engine brand Yanmar 4.70 km/h Engine brandle 4 4.70 km/h Engine brandle 4 4.70 km/h Engine brandle 4 4.70 km/h			
Dump reach - Full height 6 \$28 mm Rollback at ground a13 29 ° Rollback Angle at Full Height a4 99 ° Seat to ground height h30 853 mm Overall width less bucket b1 1346 mm Bucket Width e1 1562 mm Cround clearance m4 211 mm Overall length - Less Bucket l2 2314 mm Departure angle a2 29 ° Clearance Radius - Front with Bucket b18 1758 mm Performances Travel speed (unladen) 5 10 x 16.5 - 10 PR HD Wheels 10 x 16.5 - 10 PR HD Standard tires 10 x 16.5 - 10 PR HD Engine 4 4 TNV88 Engine model 4 4 TNV88 Engine pone 8-8-III Max. torque / Engine rotation 142 Nm / 1600 pm Power source Diesel Number of cylinders 4 4 Engine power (Hp / kW) 49 Hp / 36 kW Engine cooling system			
Rollback at ground a13 29 ° Rollback Angle at Full Height a4 99 ° Seat to ground height h30 853 mm Overall width less bucket b1 1346 mm Bucket Width e1 1562 mm Ground clearance m4 211 mm Overall length - Less Bucket 12 2314 mm Departure angle a2 29 ° Clearance Radius - Front with Bucket b18 1758 mm Performances			
Rollback Angle at Full Height a4 99 ° Seat to ground height h30 853 mm Overall width less bucket b1 1346 mm Bucket Width e1 1552 mm Ground clearance m4 211 mm Overall length - Less Bucket 12 2314 mm Operature angle a2 29 ° Clearance Radius - Front with Bucket b18 1758 mm Ferformances Travel speed (unladen) 0 10.70 km/h Wheels Travel speed (unladen) 4 10.70 km/h Wheels 10.70 km/h 10.70 km/h 10.70 km/h Wheels 10 x 16.5 10 PR HD 11 x 10 x	· · · · · ·		
Seat to ground height h30 853 mm Overall width less bucket b1 1346 mm Bucket Width e1 1562 mm Ground clearance m4 211 mm Overall length - Less Bucket 12 2314 mm Operature angle a2 29° Clearance Radius - Front with Bucket b18 1758 mm Performances	•		
Overall width less bucket b1 1346 mm Bucket Width e1 1562 mm Ground clearance m4 211 mm Overall length - Less Bucket 12 2314 mm Departure angle a2 29° Clearance Radius - Front with Bucket b18 1758 mm Feef omances b18 1758 mm Tavel speed (unladen) 5 10.70 km/h Wheels 5 10.70 km/h 10.70 km/h Engine brand 5 10 x 16.5 - 10 PR HD 10 x 16.5 - 10 PR HD Engine model 5 4 TNV88 Engine model 5 4 TNV88 Engine model 6 88-III Max. torque / Engine rotation 5 142 Nm / 1600 rpm Power source 9 0 Diesel Number of cylinders 4 4 Engine rotation 5 49 Hp / 36 kW Engine cooling system 6 49 Hp / 36 kW Engine cooling system 6 4 Alteractor Ampere			
Bucket Width e1 1552 mm Ground clearance m4 211 mm Overall length - Less Bucket l2 2314 mm Departure angle a2 29 ° Clearance Radius - Front with Bucket b18 1758 mm Performances Travel speed (unladen) 10.70 km/h Wheels Hydrostatic Standard tires 10 x 16.5 - 10 PR HD Engine Yannar Engine brand Yannar Engine brand Yannar Engine nom BS-III Max. torque / Engine rotation BS-III Max. torque / Engine rotation BS-III Max. torque / Engine rotation Diesel Number of cylinders 4 Engine power (Hp / kW) Agency (Hp / kW) Engine cooling system Water cooled Battery ovitage Alexance (SA) Atternator - Ampere 55 A Starter Alexance (SA) <			
Ground clearance m4 211 mm Overall length - Less Bucket i2 2314 mm Departure angle a2 29 ° Clearance Radius - Front with Bucket b18 1758 mm Performances Travel speed (unladen) 10.70 km/h Wheels Transmission type Hydrostatic Standard tires 10 x 16.5 - 10 PR HD Engine 10 x 16.5 - 10 PR HD Engine brand Yanmar Engine model 4TNV88 Engine norm 142 Nm / 1600 pm Power source Diesel Number of cylinders 4 Engine power (Hp / kW) 49 Hp / 36 kW Engine cooling system Water cooled Battery voltage 12 V Alternator - Ampere 55 A Stanter 3 kW Hydraulics 4			
Overall length - Less Bucket 12 2314 mm Departure angle a2 29° Clearance Radius - Front with Bucket b18 1758 mm Ferformances Travel speed (unladen) 10.70 km/h Wheels Hydrostatic Standard tires Hydrostatic Standard tires Transmission type Engine 10 x 15.5 - 10 PR HD Engine brand Engine model Yanmar Engine norm ATNV88 Engine rotation 142 Nm / 1600 rpm Power source Dimerior Number of cylinders 4 Lingine power (Hp / kW) 49 Hp / 36 kW Engine cooling system Water cooled Battery voltage 55 A Stanter 55 A Stanter 3 kW			
Departure angle a2 29° Clearance Radius - Front with Bucket b18 1758 mm Performances Travel speed (unladen) 10.70 km/h Wheels Transmission type Hydrostatic Standard tires 10 x 16.5 - 10 PR HD Engine 4 Engine brand 4 TNV88 Engine model BS-III Engine norm BS-III Max. torque / Engine rotation 142 Nm / 1600 rpm Power source Diesel Number of cylinders 4 Engine power (Hp / kW) 49 Hp / 36 kW Engine cooling system Water cooled Battery voltage 12 V Alternator - Ampere 55 A Starter 3 kW Hydraulics			
Clearance Radius - Front with Bucket b18 1758 mm Performances Travel speed (unladen) Wheels Hydrostatic Standard tires 10 x 16.5 - 10 PR HD Engine Engine brand Engine model 4 TNV88 Engine norm BS-III Max. torque / Engine rotation 142 Nm / 1600 rpm Power source Diesel Number of cylinders 4 Engine power (Hp / kW) 49 Hp / 36 kW Engine cooling system Water cooled Battery voltage 12 V Atlemator - Ampere 55 A Starter 3 kW Hydraulics	•		
Performances 10.70 km/h Wheels Hydrostatic Standard tires 10 x 16.5 - 10 PR HD Engine 10 x 16.5 - 10 PR HD Engine brand Yanmar Engine norm BS-III Max. torque / Engine rotation 142 Nm / 1600 rpm Power source Diesel Number of cylinders 4 Engine power (Hp / kW) 49 Hp / 36 kW Engine cooling system Water cooled Sattery oltage 12 V Alternator - Ampere 55 A Starter 3 kW Hydraulics	· · · · ·		
Travel speed (unladen) Wheels Transmission type Standard tires Engine Engine brand Engine model Engine norm Max. torque / Engine rotation Power source Number of cylinders Engine power (Hp / kW) Engine cooling system Battery voltage Battery voltage Altemator - Ampere Standard tires 10 x 16.5 - 10 PR HD Yanmar Yanmar 4 TNV88 BS-III 142 Nm / 1600 rpm Diesel A4 Engine cooling system Water cooled Battery voltage Altemator - Ampere Starter 3 kW Hydraulics		018	1758 mm
WheelsHydrostaticStandard tires10 x 16.5 - 10 PR HDEngine10 x 16.5 - 10 PR HDEngine brandYanmarEngine model4TNV88Engine normBS-IIIMax. torque / Engine rotation142 Nm / 1600 rpmPower sourceDieselNumber of cylinders4Engine power (Hp / kW)49 Hp / 36 kWEngine cooling systemWater cooledBattery voltage12 VAltemator - Ampere55 AStarter3 kWHydraulics15 C			10.70 km/h
Transmission type Standard tires Engine Engine brand Engine model Engine norm Max. torque / Engine rotation Power source Number of cylinders Engine power (Hp / kW) Engine cooling system Battery voltage Battery voltage Battery voltage Hydrostatic 10 x 16.5 - 10 PR HD Yanmar Yanmar FYanmar BS-III 142 Nm / 1600 rpm 142 Nm / 1600 rpm Diesel 4 Engine power (Hp / kW) Engine cooling system Battery voltage Altemator - Ampere Starter Hydroulics			10.70 km/n
Standard tires 10 x 16.5 - 10 PR HD Engine Engine Engine brand Yanmar Engine model 4TNV88 Engine norm BS-III Max. torque / Engine rotation 142 Nm / 1600 rpm Power source Diesel Number of cylinders 4 Engine power (Hp / kW) 49 Hp / 36 kW Engine cooling system Water cooled Battery voltage 12 V Alternator - Ampere 55 A Starter 3 kW Hydraulics			Hadar skalin
Engine Fund the stand Yanmar Engine model 4TNV88 Engine norm BS-III Max. torque / Engine rotation 142 Nm / 1600 rpm Power source Diesel Number of cylinders 4 Engine power (Hp / kW) 49 Hp / 36 kW Engine cooling system Water cooled Battery voltage 12 V Alternator - Ampere 55 A Starter 3 kW Hydraulics			*
Engine brand Yanmar Engine model 4TNV88 Engine norm BS-III Max. torque / Engine rotation 142 Nm / 1600 rpm Power source Diesel Number of cylinders 4 Engine power (Hp / kW) 49 Hp / 36 kW Engine cooling system Water cooled Battery voltage 12 V Alternator - Ampere 55 A Starter 3 kW			10 X 16.5 - 10 PR HD
Engine model 4TNV88 Engine norm BS-III Max. torque / Engine rotation 142 Nm / 1600 rpm Power source Diesel Number of cylinders 4 Engine power (Hp / kW) 49 Hp / 36 kW Engine cooling system Water cooled Battery voltage 12 V Alternator - Ampere 55 A Starter 3 kW Hydraulics Wester cooled			
Engine norm BS-III Max. torque / Engine rotation 142 Nm / 1600 rpm Power source Diesel Number of cylinders 4 Engine power (Hp / kW) 49 Hp / 36 kW Engine cooling system Water cooled Battery voltage 12 V Alternator - Ampere 55 A Starter 3 kW Hydraulics 6	•		
Max. torque / Engine rotation 142 Nm / 1600 rpm Power source Diesel Number of cylinders 4 Engine power (Hp / kW) 49 Hp / 36 kW Engine cooling system Water cooled Battery voltage 12 V Alternator - Ampere 55 A Starter 3 kW Hydraulics	•		
Power source Diesel Number of cylinders 4 Engine power (Hp / kW) 49 Hp / 36 kW Engine cooling system Water cooled Battery voltage 12 V Alternator - Ampere 55 A Starter 3 kW Hydraulics 6	•		
Number of cylinders 4 Engine power (Hp / kW) 49 Hp / 36 kW Engine cooling system Water cooled Battery voltage 12 V Alternator - Ampere 55 A Starter 3 kW Hydraulics 6	· · ·		·
Engine power (Hp / kW) 49 Hp / 36 kW Engine cooling system Water cooled Battery voltage 12 V Alternator - Ampere 55 A Starter 3 kW Hydraulics 6			
Engine cooling system Water cooled Battery voltage 12 V Altemator - Ampere 55 A Starter 3 kW Hydraulics 6	·		
Battery voltage 12 V Alternator - Ampere 55 A Starter 3 kW Hydraulics 6			•
Alternator - Ampere 55 A Starter 3 kW Hydraulics	· · · · ·		
Starter 3 kW Hydraulics	• •		
Hydraulics			
			3 kW
Auxiliary Hydraulic Pressure 190 bar	Hydraulics		
	Auxiliary Hydraulic Pressure		190 bar
High-Flow Auxiliary Hydraulics - Option 63.40 I/min			63.40 l/min
Tank capacities			
Fuel 47 I	Fuel		47 I
Hydraulic tank capacity 30.30 I	Hydraulic tank capacity		30.30 l
Displacement 2.20 I	Displacement		2.20
Cooling liquid 7.60 l	Cooling liquid		7.60 l
LH Chain case 8.25 I	LH Chain case		8.25
DI Obsis and	RH Chain case		8.25 I

1340R - Dimensional drawing







Equipment

Lifting function	
All-Tach® Attachment Mounting System	Standard
Auxiliary Hydraulics	Standard
Lighting	
Work Lights - Front and Rear	Standard
Motorization/Power	
Engine Block Heater	Standard
Operator station	
Cabin Rops and fops level I	Standard
Hand/Foot Controls	Optional
Horn	Optional
Sound Reduction Material	Standard
Suspension Seat - Mechanical	Standard
T-Bar control	Standard
Other options	
Selectable Self-Leveling Hydraulic Lift Action 4	Optional
Pneumatics	
Camso Tyres Option	Optional
Secondary functions	
Full Instrumentation	Standard
Security	
Anti-Vandalism Protection	Standard
Back-Up Alarm	Optional
Hydraloc™ Safety System	Standard
Operator Restraint Bar	Standard





Head Office

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes