

Technical sheet :

1850RT



 **MANITOU**
HANDLING YOUR WORLD

| Capacities | | Metric |
|---|-----|--|
| Max. capacity | Q | 2398 kg |
| Operating Weight | | 4128 kg |
| Unladen weight | | 4128 kg |
| Operating Capacity at 35% Tipping Load | | 839 kg |
| Operating Capacity At 50% Tipping Load | | 1199 kg |
| Tipping capacity | | 2398 kg |
| Weight and dimensions | | |
| Overall Operating Height - Fully Raised | h27 | 4267 mm |
| Height to Hinge Pin – Fully Raised | h28 | 3251 mm |
| Dump reach - Full height | r6 | 876 mm |
| Dump angle at full height | a5 | 40.20 ° |
| Dump Height - Fully Raised | h29 | 2489 mm |
| Maximum Rollback Angle - Fully Raised | a4 | 102.50 ° |
| Overall Height to top of ROPS | h17 | 2103 mm |
| Overall length with bucket | l16 | 3754 mm |
| Overall Length without Bucket | l1 | 2921 mm |
| Specified Height | h31 | 1715 mm |
| Reach at Specified Height | r4 | 790 mm |
| Dump angle at specified height | a17 | 66.80 ° |
| Maximum Rollback Angle at Ground | a13 | 30 ° |
| Carry Position | d5 | 208 mm |
| Maximum Rollback Angle at Carry Position | a14 | 31.60 ° |
| Digging Position | h32 | 23 mm |
| Angle of Departure with STD Counterweight | | 30.40 ° |
| Ground clearance | m4 | 318 mm |
| Track gauge | b10 | 1313 mm |
| Track Shoe Width | b20 | 320 mm |
| Crawler base | y2 | 1392 mm |
| Overall width less bucket | b1 | 1636 mm |
| Bucket Width | e1 | 1674 mm |
| Clearance Radius - Front with Bucket | b18 | 2322 mm |
| Clearance Circle - Rear | wa1 | 1666 mm |
| Maximum rollback at specified height | | 66.80 ° |
| Angle of Approach | a3 | 90 ° |
| Grouser Height | | 25 mm |
| Track Type / Track Rollers / Roller Type | | Rubber / 4 / Steel |
| Performances | | |
| Ground Speed - Single Speed | | 9.50 km/h |
| Ground Speed - Two Speed | | 14.20 km/h |
| Drawbar Pull/Traction Effort | | 4635 kg |
| Bucket Breakout - Tilt Cylinder | | 2429 kg |
| Bucket Breakout - Lift Cylinder | | 2275 kg |
| Engine | | |
| Engine brand | | Yanmar |
| Engine model | | 4TNV98C-NMSL |
| Motor Type | | Axial Piston with Planetary Gear Box Reduction |
| Gross Power / Power | | 51.70 kW @ 2500 rpm |
| Net Power / Power | | 51 kW / 2500 rpm |
| Max. torque | | 241 Nm |
| I.C. Engine power rating | | 69.30 Hp |
| Battery voltage | | 12 V |
| Cold Cranking Amps at Temperature (CCA) | | 850 A |
| Alternator - Voltage / Ampere | | 14 V / 100 A |
| Tank capacities | | |
| Oil Pan Capacity | | 10.40 l |
| Hydraulic oil tank capacity | | 41.60 l |
| Fuel tank | | 91 l |
| Coolant system capacity | | 13.30 l |
| Displacement / Number of cylinders | | 3.30 l / 4 |
| Miscellaneous | | |
| Ground Pressure | | 0.43 bar |

Tilt-out Foot Pod



Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes