

Technical sheet :

2550RT



 **MANITOU**
HANDLING YOUR WORLD

| Capacities | | Imperial |
|---|-----|---|
| Max. capacity | Q | 7286 lb |
| Operating Weight | | 11596 lb |
| Unladen weight | | 11596 lb |
| Operating Capacity at 35% Tipping Load | | 2551 lb |
| Operating Capacity At 50% Tipping Load | | 3642 lb |
| Tipping capacity | | 7286 lb |
| Weight and dimensions | | |
| Overall Operating Height - Fully Raised | h27 | 168 in |
| Height to Hinge Pin - Fully Raised | h28 | 128 in |
| Dump reach - Full height | r6 | 34 in |
| Dump angle at full height | a5 | 41 ° |
| Dump Height - Fully Raised | h29 | 98 in |
| Maximum Rollback Angle - Fully Raised | a4 | 102.50 ° |
| Overall Height to top of ROPS | h17 | 83 in |
| Overall length with bucket | l16 | 158 in |
| Departure angle | a2 | 25 ° |
| Overall Length without Bucket | l1 | 127 in |
| Specified Height | h31 | 68 in |
| Reach at Specified Height | r4 | 31 in |
| Dump angle at specified height | a17 | 66.80 ° |
| Carry Position | d5 | 8 in |
| Maximum Rollback Angle at Carry Position | a14 | 31.60 ° |
| Digging Position | h32 | 0.51 in |
| Angle of Departure with STD Counterweight | | 25 ° |
| Ground clearance | m4 | 12 in |
| Track gauge | b10 | 52 in |
| Track Shoe Width | b20 | 18 in |
| Crawler base | y2 | 61 in |
| Overall width less bucket | b1 | 69 in |
| Bucket Width | e1 | 84 in |
| Clearance Radius - Front with Bucket | b18 | 98 in |
| Angle of Approach | a3 | 90 ° |
| Grouser Height | | 0.98 in |
| Track Type / Track Rollers / Roller Type | | Rubber / 5 / Steel |
| Performances | | |
| Ground Speed - Single Speed | | 5 mph |
| Ground Speed - Two Speed | | 8 mph |
| Drawbar Pull/Tractive Effort | | 12454 lb |
| Bucket Breakout - Tilt Cylinder | | 8384 lb |
| Bucket Breakout - Lift Cylinder | | 7436 lb |
| Engine | | |
| Engine brand | | Deutz |
| Engine model | | TD 3.6 L4 |
| Motor Type | | Axial Piston Planetary Gear Box Reduction |
| Engine power (Hp) | | 72 Hp |
| Engine power (kW) | | 52.70 kW |
| Max. torque | | 243 ft/lbs |
| Battery voltage | | 12 V |
| Cold Cranking Amps at Temperature (CCA) | | 950 A |
| Alternator - Voltage / Ampere | | 12 V / 120 A |
| Hydraulics | | |
| Standard flow - Auxiliary hydraulics | | 29 US gpm |
| Tank capacities | | |
| Oil Pan Capacity | | 2 US gal |
| Hydraulic tank capacity | | 14 US gal |
| Fuel tank capacity | | 32 US gal |
| Cooling liquid | | 6 US gal |
| Displacement / Number of cylinders | | 0.95 US gal / 4 |
| Noise and vibration | | |
| Noise to environment (LwA) | | 106.10 dB |
| Noise at driving position (LpA) | | 85.80 dB |
| Miscellaneous | | |
| Ground Pressure | | 5 PSI |

Equipment

| | |
|--|----------|
| Lifting function | |
| All-Tach® Attachment Mounting System | Standard |
| Auxiliary Hydraulics | Standard |
| Electronic Attachment Control - 14-Pin Connector | Optional |
| High-Flow Auxiliary Hydraulics | Optional |
| IdealTrax® automatic track tensioning system | Standard |
| Power-A-Tach® Attachment Mounting System | Optional |
| Motorization/Power | |
| Combination Radiator & Hydraulic Oil Cooler | Standard |
| Dual-Element Air Cleaner with Indicator | Standard |
| Elevated Planetary Final Drives | Standard |
| Engine Auto-Shutdown System | Standard |
| Glowplugs Starts Assist | Standard |
| Horsepower Management System | Standard |
| Two-Speed Hydrostatic Drive System | Standard |
| Operator station | |
| Air suspension seat | Optional |
| Drive Sensitivity Adjustment | Standard |
| Electro-Hydraulic Joystick Controls | Standard |
| Foot Throttle | Standard |
| Full-Suspension Seat | Standard |
| IdealAccess™ Fold-Up Door | Optional |
| Multi-Function Display Screen | Standard |
| Pressurized Cab Enclosure with A/C | Optional |
| Rearview Camera | Standard |
| ROPS/FOPS Level II Overhead Guard | Standard |
| Sliding Side Windows | Standard |
| Swing-out Cab Door | Standard |
| Variable Speed Control, Selectable On & Off | Optional |
| Other options | |
| Selectable Self-Leveling Hydraulic Lift Action 4 | Optional |
| Pneumatics | |
| Rubber Track Undercarriage System | Standard |
| Single Flange Front/Dual Flange Rear Idlers | Standard |
| Secondary functions | |
| Counterweight | Standard |
| Dedicated Undercarriage | Standard |
| Security | |
| Anti-Vandalism Lock Provisions | Standard |
| Back-Up Alarm | Standard |
| Easy Manager | Standard |
| Engine Alert System with Error Display | Standard |
| Mechanical Lift Cylinder Lock | Standard |
| Straight Tracking | Standard |
| Tilt-out Foot Pod | Standard |



Head Office

B.P. 249 - 430 rue de l'Aubinière
44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes