Technical sheet:

## **CMT 270**





CMT 270 Created on 27 April 2024 at 11:59:46 AM UTC

	Ent 220 oreated on 27 rpm 2021 at 111031 to 7441 ore
Capacities	Metric
Drum volume	270
Mixing capacity	220
Performances	
Power source	Gasoline
Technical characteristics	
Base unit part number	52737760
Ring towing bar type	52737760
Ball towing bar type	52737761
Unladen weight	280 kg
Tilting wheel diameter	625 mm
Engine	
Engine brand	Worms & Robin





## **Head Office**

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes