Technical sheet:


CMT 400





CMT 400 Created on June 16, 2025 at 3:34 PM UTC

Capacities	Metric
Drum volume	400 l
Mixing capacity	340 I
Performances	
Power source	Gasoline
Technical characteristics	
Base unit part number	52737768
Ring towing bar type	52737768
Ball towing bar type	52737769
Unladen weight	300 kg
Tilting wheel diameter	625 mm





Head Office

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes