Technical sheet:

## **CMT 400**





|                           | •        |
|---------------------------|----------|
| Capacities                | Metric   |
| Drum volume               | 400 l    |
| Mixing capacity           | 340      |
| Performances              |          |
| Power source              | Gasoline |
| Technical characteristics |          |
| Base unit part number     | 52737768 |
| Ring towing bar type      | 52737768 |
| Ball towing bar type      | 52737769 |
| Unladen weight            | 300 kg   |
| Tilting wheel diameter    | 625 mm   |
|                           |          |





## **Head Office**

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes